

### 43562.2 Information



For Reference Only

**Part Number** 43562.2

ManufacturerOn Shore Technology Inc.CategoryConnectors, Interconnects

Terminal Blocks - Din Rail, Channel

**Description** CONN TERM BLK FEED THRU 12-20AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 43562.2 Specifications

Manufacturer Part Number         43562.2           Manufacturer         On Shore Technology Inc.           Category         Connectors, Interconnects           Package         -           Series         ZRD2.5           Type         Feed Through           Disconnect Type         -           Number of Positions         4           Number of Levels         2           Terminal - Width         5.1mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         500V           Current - UL         10A           Voltage - UL         300V           Wire Gauge or Range - AWG         12-20 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Beige		
Category         Connectors, Interconnects           Package         -           Series         ZRD2.5           Type         Feed Through           Disconnect Type         -           Number of Positions         4           Number of Levels         2           Terminal - Width         5.1mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         500V           Current - UL         10A           Voltage - UL         300V           Wire Gauge or Range - AWG         12-20 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Beige	Manufacturer Part Number	43562.2
Package         -           Series         ZRD2.5           Type         Feed Through           Disconnect Type         -           Number of Positions         4           Number of Levels         2           Terminal - Width         5.1mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         500V           Current - UL         10A           Voltage - UL         300V           Wire Gauge or Range - AWG         12-20 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Beige	Manufacturer	On Shore Technology Inc.
Package         -           Series         ZRD2.5           Type         Feed Through           Disconnect Type         -           Number of Positions         4           Number of Levels         2           Terminal - Width         5.1mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         500V           Current - UL         10A           Voltage - UL         300V           Wire Gauge or Range - AWG         12-20 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Beige	Category	Connectors, Interconnects
SeriesZRD2.5TypeFeed ThroughDisconnect Type-Number of Positions4Number of Levels2Terminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 500V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige	Package	-
Disconnect Type  Number of Positions  4  Number of Levels  2  Terminal - Width  5.1mm  Termination Style  Push In, Spring  Current - IEC  24A  Voltage - IEC  500V  Current - UL  10A  Voltage - UL  Wire Gauge or Range - AWG  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  Color  Beige	Series	ZRD2.5
Number of Positions4Number of Levels2Terminal - Width5.1 mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Туре	Feed Through
Number of Levels         2           Terminal - Width         5.1mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         500V           Current - UL         10A           Voltage - UL         300V           Wire Gauge or Range - AWG         12-20 AWG           Wire Gauge or Range - mm²         0.5-4mm²           Features         -           Color         Beige	Disconnect Type	-
Terminal - Width  Termination Style  Push In, Spring  Current - IEC  24A  Voltage - IEC  500V  Current - UL  10A  Voltage - UL  300V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  -  Color  Beige	Number of Positions	4
Termination Style  Current - IEC  24A  Voltage - IEC  500V  Current - UL  10A  Voltage - UL  300V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  -  Color  Push In, Spring  24A  24A  500V  500V  500V  500V  10A  300V  800  10-20 AWG  12-20 AWG  80-5-4mm²  Features  -  Color  Beige	Number of Levels	2
Current - IEC       24A         Voltage - IEC       500V         Current - UL       10A         Voltage - UL       300V         Wire Gauge or Range - AWG       12-20 AWG         Wire Gauge or Range - mm²       0.5-4mm²         Features       -         Color       Beige	Terminal - Width	5.1mm
Voltage - IEC500VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Termination Style	Push In, Spring
Current - UL       10A         Voltage - UL       300V         Wire Gauge or Range - AWG       12-20 AWG         Wire Gauge or Range - mm²       0.5-4mm²         Features       -         Color       Beige	Current - IEC	24A
Voltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Voltage - IEC	500V
Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Color  12-20 AWG  0.5-4mm²  -  Beige	Current - UL	10A
Wire Gauge or Range - mm²  Features  Color  Beige	Voltage - UL	300V
Features - Color Beige	Wire Gauge or Range - AWG	12-20 AWG
Color Beige	Wire Gauge or Range - mm <sup>2</sup>	0.5-4mm <sup>2</sup>
	Features	-
Report errors?	Color	Beige
		Report errors?

### 43562.2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 43562.2 Payment Methods



















# 43562.2 Shipping Methods













If you have any question about 43562.2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com