

450MXG270MEFCSN25X40

450MXG270MEFCSN25X40 Information



For Reference Only

Part Number 450MXG270MEFCSN25X40

Manufacturer Rubycon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 270UF 20% 450V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









450MXG270MEFCSN25X40 Specifications

Manufacturer Part Number450MXG270MEFCSN25X40ManufacturerRubyconCategoryCapacitorsPackageRadial, Can - Snap-InSeriesMXGCapacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series MXG Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance - Capacitors Capacitors Radial, Can - Snap-In MXG 270µF -20% 450V -20% -20% -20% -20% -20% -20% -20% -20%	Manufacturer Part Number	450MXG270MEFCSN25X40
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesMXGCapacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-	Manufacturer	Rubycon
PackageRadial, Can - Snap-InSeriesMXGCapacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-	Category	Capacitors
SeriesMXGCapacitance 270μ FTolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-		Aluminum Electrolytic Capacitors
Capacitance270μFTolerance±20%Voltage - Rated450 VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Series	MXG
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 450V	Capacitance	270μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance -	Tolerance	±20%
Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance	Voltage - Rated	450V
Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Polarization	Polar
Ripple Current - High Frequency - Impedance -	Applications	General Purpose
Impedance -	Ripple Current - Low Frequency	-
	Ripple Current - High Frequency	-
Lead Spacing 0.394" (10.00mm)	Impedance	-
	Lead Spacing	0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)	Size / Dimension	0.984" Dia (25.00mm)
Height - Seated (Max) 1.654" (42.00mm)	Height - Seated (Max)	1.654" (42.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

450MXG270MEFCSN25X40 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

450MXG270MEFCSN25X40 Payment Methods



















450MXG270MEFCSN25X40 Shipping Methods













If you have any question about 450MXG270MEFCSN25X40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com