

4515DO-DS3BK005GP

4515DO-DS3BK005GP Information

Part Number 4515DO-DS3BK005GP

Manufacturer TE Connectivity Measurement Specialties

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS GAUGE

Package 8-DIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4515DO-DS3BK005GP Specifications

Manufacturer Part Number 4515DO-DS3BK005GP Manufacturer TE Connectivity Measurement Specialties Category Sensors, Transducers Package 8-DIP Module Series - Pressure Type Vented Gauge Operating Pressure 0.18 PSI (1.25 kPa) Output Type 12C Output 14 b Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package - Report errors?		
Category Sensors, Transducers Pressure Sensors, Transducers Package 8-DIP Module Series - Pressure Type Vented Gauge Operating Pressure Output Type I2C Output 14 b Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Tempination Style Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature Package / Case 8-DIP Module Supplier Device Package - Suppl Maximum Preskage - Suppl Module Supplier Device Package - Suppl Module	Manufacturer Part Number	4515DO-DS3BK005GP
Package 8-DIP Module Series - Pressure Type Vented Gauge Operating Pressure Output Type 12C Output 14 b Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature Package / Case 8-DIP Module Supplier Device Package	Manufacturer	TE Connectivity Measurement Specialties
Package 8-DIP Module Series - Pressure Type Vented Gauge Operating Pressure 0.18 PSI (1.25 kPa) Output Type 12C Output 14 b Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Category	Sensors, Transducers
Series - Pressure Type Vented Gauge Operating Pressure 0.18 PSI (1.25 kPa) Output Type 12C Output 14 b Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 0.18 PSI (1.25 kPa) Output Type 12C Output 14 b Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package	Package	8-DIP Module
Operating Pressure Output Type I2C Output 14 b Accuracy ±0.25% Voltage - Supply Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature Package / Case Supplier Device Package - 0.18 PSI (1.25 kPa) 0.18 PSI (1.25 kPa) 14 b 14 b 14 b 14 b 16 c 17 c 18 c 19 c 10 PSI (68.95 kPa) -10°C ~ 85°C 8-DIP Module 10 PSI (68.95 kPa) -10°C ~ 85°C	Series	-
Output TypeI2COutput14 bAccuracy±0.25%Voltage - Supply3.3VPort SizeMale - 0.14" (3.56mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-10°C ~ 85°CPackage / Case8-DIP ModuleSupplier Device Package-	Pressure Type	Vented Gauge
Output 14 b Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature - 10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Operating Pressure	0.18 PSI (1.25 kPa)
Accuracy ±0.25% Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Output Type	I2C
Voltage - Supply 3.3V Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Output	14 b
Port Size Male - 0.14" (3.56mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Accuracy	$\pm 0.25\%$
Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Voltage - Supply	3.3V
Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Port Size	Male - 0.14" (3.56mm) Tube, Dual
Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Port Style	Barbed
Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Features	Temperature Compensated
Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package -	Termination Style	PC Pin
Package / Case 8-DIP Module Supplier Device Package -	Maximum Pressure	10 PSI (68.95 kPa)
Supplier Device Package -	Operating Temperature	-10°C ~ 85°C
	Package / Case	8-DIP Module
Report errors?	Supplier Device Package	-
		Report errors?

4515DO-DS3BK005GP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4515DO-DS3BK005GP Payment Methods



















4515DO-DS3BK005GP Shipping Methods













If you have any question about 4515DO-DS3BK005GP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com