

4MA075000Z4AACTGI

4MA075000Z4AACTGI Information

Heisener.com	4MA075000Z4AACTGI IDT, Integrated Device Technology Inc Crystals, Oscillators, Resonators Oscillators OSC MEMS 75.000MHZ LVDS SMD 6-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



4MA075000Z4AACTGI Specifications

AnufacturerIDT, Integrated Device Technology IncCategoryCrystals, Oscillators, ResonatorsPackageOscillatorsPackage6-SMD, No LeadSeries4MACypeMEMS (Silicon)Frequency75MHzFunctionEnable/DisableDutputLVDSOrdge - Supply3.3VOperating Temperature40°C ~ 85°CCurrent - Supply (Max)5.0rgan (Typ)Ratings-Package / Case6.SMD, No LeadBackage / Case6.SMD, No LeadBizer / Dimension0.017" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage6-SMD, No LeadBackage4MASteries4MAStypeMEMS (Silicon)Prequency75MHzPonctionEnable/DisableDutputLVDSVoltage - Supply3.3VPrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Package / Case6-SMD, No LeadBize / Dimension0.035" (0.90mm)	Manufacturer Part Number	4MA075000Z4AACTGI
OscillatorsPackage6-SMD, No LeadBeries4MATypeMEMS (Silicon)Srequency75MHzPunctionEnable/DisableDutputLVDSVoltage - Supply3.3VSrequency Stability±50ppmOperating Temperature40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Aunting TypeSurface MountPackage / Case6-SMD, No LeadBize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Manufacturer	IDT, Integrated Device Technology Inc
Package 6-SMD, No Lead Genes 4MA Sype MEMS (Silicon) Frequency 75MHz Punction Enable/Disable Output LVDS Voltage - Supply 3.3V Prequency Stability ±50pm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 105mA (Typ) Ratings - Package / Case 6-SMD, No Lead Bizer / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
Series4MASppeMEMS (Silicon)Spequency75MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VSrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Adounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)		Oscillators
TypeMEMS (Silicon)Grequency75MHzFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VGrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Adounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Package	6-SMD, No Lead
Arroy75MHzFrequencyFnable/DisableFunctionEnable/DisableDutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Aounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Series	4MA
FunctionEnable/DisableDutputLVDSVoltage - Supply3.3VSrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Aounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Туре	MEMS (Silicon)
DutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Aounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Frequency	75MHz
A3.3VSrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Catings-Aounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Function	Enable/Disable
Frequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Output	LVDS
Operating Temperature-40°C ~ 85°CCurrent - Supply (Max)105mA (Typ)Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadBize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Voltage - Supply	3.3V
Current - Supply (Max)105mA (Typ)Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Frequency Stability	±50ppm
Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadPackage / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Operating Temperature	-40°C ~ 85°C
Mounting TypeSurface MountPackage / Case6-SMD, No LeadBize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Current - Supply (Max)	105mA (Typ)
Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Mounting Type	Surface Mount
Height - Seated (Max)0.035" (0.90mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Dependence of the second	Height - Seated (Max)	0.035" (0.90mm)
Report errors?		Report errors?

4MA075000Z4AACTGI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

4MA075000Z4AACTGI Payment Methods



If you have any question about 4MA075000Z4AACTGI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com