

5246AB16X371 Information

Heisener.com

For Reference Only

Part Number 5246AB16X371
Manufacturer APEM Inc.
Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5246AB16X371 Specifications

Manufacturer APEM Inc. Category Switches Package - Series 5000 Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 8.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series5000CircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length8.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	5246AB16X371
Package - Series 5000 Circuit DPDT Switch Function On-On Current Rating AC 125V Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round 8.50mm Illumination Type, Color 11lumination Type, Color 11lumination Type, Color 11lumination Voltage (Nominal) - Monuting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Manufacturer	APEM Inc.
Package - Series 5000 Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 8.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 5000 Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 8.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard RoundActuator Length8.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length8.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	5000
Current Rating6A (AC), 4A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard RoundActuator Length8.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length8.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 8.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Current Rating	6A (AC), 4A (DC)
Actuator Type Standard Round Actuator Length 8.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length Bulliumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Length	8.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Panart awars?	Features	Epoxy Sealed Terminals
Report errors?		Report errors?

5246AB16X371 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5246AB16X371 Payment Methods



















5246AB16X371 Shipping Methods













If you have any question about 5246AB16X371, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com