

5642MAB

5642MAB Information

Heisener.com Gistal tervez stadt ter	Part Number Manufacturer Category Description Package	5642MAB APEM Inc. Switches Toggle Switches SWITCH TOGGLE DPDT 6A 125V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5642MAB Specifications

ManufacturerAPEM Inc.CategorySwitchesPackage-Package-Series5000CircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC30VVoltage Rating - DCSandard RoundActuator TypeSandard RoundIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mouting TypePanel MouttFermination StyleSolder Lug		
CategorySwitchesPackage-Series5000CircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC30VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIllumination-Illumination Type, Color-Illumination Voltage Nominal)-Actuator SyleSolder LugMouting TypeSolder LugIllumination SyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Seaded Terminals	Manufacturer Part Number	5642MAB
Toggle SwitchesPackage-Series5000CircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	APEM Inc.
Package-Series5000CircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Mouting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
Series5000CircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC30VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50nmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel Cutout DimensionsSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStalder LugTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	5000
Current Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandar RoundActuator Type17.50mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugPanel Cutout DimensionsIsrcular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Mom
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsIS/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	6A (AC), 4A (DC)
Actuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	30V
IluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Ilumination Type, Color-Ilumination Yoltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	17.50mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 12.50mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 12.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	15/32-32
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

5642MAB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 5642MAB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com