

5973401407F

5973401407F Information



Part Number	5973401407F	
Manufacturer	Dialight	
Category	Optoelectronics LED Indication - Discrete	
Description	LED YELLOW CLEAR 2SMD	
Package	2-SMD, No Lead	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5973401407F Specifications

ManufacturerDialightCategoryOptoelectronicsLED Indication - DiscretePackage2-SMD, No LeadPackagemicroLED?ColorYellowConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela RatingmcdVoltage - Forward (Vf) (Typ)2.2VCurrent - TestSurface MountViewing AngleSurface MountWavelength - Peak590nmWavelength - Peak580nmFeatures-Package / Case2.SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm Lx 1.50mm WHeight (Max)1.69mm	-	
Category Optoelectronics LED Indication - Discrete Package 2-SMD, No Lead Package 2-SMD, No Lead Series microLED? Color Yellow Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 6mcd Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Voleing Angle 70° Mounting Type Surface Mount Wavelength - Poninant 590nm Vavelength - Peak 580nm Features - Package / Case 2.SMD, No Lead Supplier Device Package 1206 Size / Dimension 3.00mm L x 1.50mm W	Manufacturer Part Number	5973401407F
LED Indication - DiscretePackage2-SMD, No LeadSeriesmicroLED?ColorYellowConfiguration-Lens ColorColorlessLens TransparencyGlearMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Dominant590nmVavelength - Peak580nmFeatures-Package / Case2.SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Manufacturer	Dialight
Package2-SMD, No LeadSeriesmicroLED?ColorYellowConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAWouting TypeSurface MountWavelength - Dominant590nmVavelength - Peak580nmFeatures-Package / Case2.SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Category	Optoelectronics
SeriesmicroLED?ColorYellowConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Peak590nmFeatures-Package / Case2.5MD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm		LED Indication - Discrete
ColorYellowConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAVoltaging AngleSurface MountMounting TypeSurface MountWavelength - Dominant590nmFeatures-Package / Case2.5MD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Package	2-SMD, No Lead
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAMunting Type70°Mounting TypeSurface MountWavelength - Dominant590nmVavelength - Peaka580nmFeatures-Package / Case2.SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm Lx 1.50mm WHeight (Max)1.69mm	Series	microLED?
Lens TolorColorlessLens TransparencyClearMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Dominant590nmVavelength - Peak580nmFeatures-Package / Case2.SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Color	Yellow
Lens TransparencyClearMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Peak590nmFeatures-Package / Case2.SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Configuration	-
Millicandela Rating6mcdMillicandela Rating6mcdLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Dominant590nmWavelength - Peak580nmFeatures-Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Lens Color	Colorless
Lens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Dominant590nmWavelength - Peak580nmFeatures-Package / Case2.SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Dominant590nmWavelength - Peak580nmFeatures-Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Millicandela Rating	6mcd
Current - Test20mAViewing Angle70°Mounting TypeSurface MountWavelength - Dominant590nmWavelength - Peak580nmFeatures-Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Lens Style/Size	Round with Flat Top
Viewing Angle70°Mounting TypeSurface MountWavelength - Dominant590nmWavelength - Peak580nmFeatures-Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Voltage - Forward (Vf) (Typ)	2.2V
Nounting TypeSurface MountWavelength - Dominant590nmWavelength - Peak580nmFeatures-Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Current - Test	20mA
Wavelength - Dominant590nmWavelength - Peak580nmFeatures-Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Viewing Angle	70°
Wavelength - Peak 580nm Features - Package / Case 2-SMD, No Lead Supplier Device Package 1206 Size / Dimension 3.00mm L x 1.50mm W Height (Max) 1.69mm	Mounting Type	Surface Mount
Features-Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Wavelength - Dominant	590nm
Package / Case2-SMD, No LeadSupplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Wavelength - Peak	580nm
Supplier Device Package1206Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Features	-
Size / Dimension3.00mm L x 1.50mm WHeight (Max)1.69mm	Package / Case	2-SMD, No Lead
Height (Max) 1.69mm	Supplier Device Package	1206
	Size / Dimension	3.00mm L x 1.50mm W
Report errors?	Height (Max)	1.69mm
		Report errors?

5973401407F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about 5973401407F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com