

6605814-8 Information

Heisener.com

Part Number 6605814-8

Manufacturer TRP Connector B.V.

Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 1PORT 1000 BASE-T

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6605814-8 Specifications

Manufacturer Part Number 6605814-8 Manufacturer TRP Connector B.V. Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series MagJack? Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Green - Yellow Number of Cores per Jack 12 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C		
Canectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series MagJack? Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.2 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Operating Temperature Operating Temperature Orientation Connectors Jack With Magnetics Nadack With Magnetics 1 Applications NagJack? RagJack With Magnetics Nadack With Magnetics Nadack With Magnetics Applicates With Magnetics Nadack With Magnetics 1 Applicates With Magnetics NagJeks With Magnetics Nadack With Magnetics 1 Applicates With Magnetics NagJeks With Magnetics 1 Applicates With M	Manufacturer Part Number	6605814-8
Package-SeriesMagJack?Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorGreen - YellowNumber of Cores per Jack12ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer	TRP Connector B.V.
Package-SeriesMagJack?Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorGreen - YellowNumber of Cores per Jack12ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Category	Connectors, Interconnects
SeriesMagJack?Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorGreen - YellowNumber of Cores per Jack12ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Green - Yellow Number of Cores per Jack 12 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature	Package	-
Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Green - Yellow Number of Cores per Jack 12 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Series	MagJack?
Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorGreen - YellowNumber of Cores per Jack12ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board LED Color Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Operating Temperature 10/100/1000 Base-T, AutoMDIX Rateound Rateound 10/100/1000 Base-T, AutoMDIX 10/1000 Base-T, AutoMDIX 10/1000 Base-T, AutoMDIX 10/1000 Base-	Number of Ports	1
Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorGreen - YellowNumber of Cores per Jack12ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Green - Yellow Number of Cores per Jack 12 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10/100/1000 Base-T, AutoMDIX
Termination Solder Height Above Board 0.555" (14.10mm) LED Color Green - Yellow Number of Cores per Jack 12 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board LED Color Green - Yellow Number of Cores per Jack 12 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0.555" (14.10mm) 6reen - Yellow 12 Number of Cores per Jack 12 Shielded, EMI Finger Board Lock Top Gord Operating Temperature 0.555" (14.10mm) Operation Green - Yellow 10 Operation Op	Orientation	90° Angle (Right)
LED ColorGreen - YellowNumber of Cores per Jack12ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 12	Height Above Board	0.555" (14.10mm)
Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	LED Color	Green - Yellow
Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	12
Tab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Shielding	Shielded, EMI Finger
Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Features	Board Lock
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Up
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
Report errors?	Operating Temperature	0°C ~ 70°C
		Report errors?

6605814-8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6605814-8 Payment Methods



















6605814-8 Shipping Methods













If you have any question about 6605814-8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com