

672D685H100CC2D

672D685H100CC2D Information

G	Heisener.com	Part Number Manufacturer Category Description Package	672D685H100CC2D Vishay Sprague Capacitors Aluminum Electrolytic Capacitors CAP ALUM 6.8UF 100V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
Fo	or Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



672D685H100CC2D Specifications

ManufacturerVishay SpragueCategoryCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, CanSeries672DCapacitance6.8µFTolerance100VVoltage - Rated100VESR (Equivalent Series Resistance)-Operating Temperature-Operating TemperatureSo°c ~ 105°CPolarizationGeneral PurposeRiple Current - High Frequency-Riple Current - High Frequency-Impedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm, Dimension)Height - Seated (Max)5.65° (14.30mm, Dimension)Surface Mount Land Size-Mounting TypeThrough Hole	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackage672DCapacitance6.8µFTolerance-Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Package / CaseRatial, Can	Manufacturer Part Number	672D685H100CC2D
Aluminum Electrolytic CapacitorsPackageRadial, CanPackage672DCapacitance6.8µFTolerance-Voltage - Rated100VESR (Equivalent Series Resistance)-Operating Temperature-Operating Temperature-ApplicationsSc° < 105°C < 105°C	Manufacturer	Vishay Sprague
PackageRadial, CanSeries672DCapacitance6.8µFTolerance-Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Size / Dimension0.197" (5.00mm)Size / Dimension0.563" (14.30mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
Series672DCapacitance6.8μFTolerance-Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance6.8µFTolerance-Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Package / CaseMail (Can	Package	Radial, Can
Tolerance.Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-S5°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Jippe Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.563" (14.30mm)Height - Seated (Max)S.653" (14.30mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	672D
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Hight - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Pounting TypeRational CancelPackage / CaseRational Cancel	Capacitance	6.8µF
ESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeRadial, Can	Tolerance	-
Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	100V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeFunculationPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	-
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-55^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.563" (14.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.563" (14.30mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

672D685H100CC2D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

672D685H100CC2D Payment Methods





If you have any question about 672D685H100CC2D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com