

6TPE150MI

lest a Quote

6TPE150MI Information

1	Part Number	6TPE150MI	
www.heisener.com		Panasonic Electronic Components	
	Category	Capacitors Tantalum - Polymer Capacitors	- 53
	Description	CAP TANT POLY 150UF 6.3V 2917	- 28
	Package	2917 (7343 Metric)	
•	-	For the pricing/inventory/lead time, please contact us	١
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



6TPE150MI Specifications

Manufacturer Part Number GTPE150MI Manufacturer Panasonic Electronic Components Category Capacitors Category Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Package 2917 (7343 Metric) Series POSCAP? TPE Capacitance 150µF Tolerance ±20% Voltage - Rated 6.3V Type Molded Poscapartine Resistance) 18 mOhm Operating Temperature - Operating Temperature 917 (7343 Metric) Munting Type Surface Mount Package / Case 2917 (7343 Metric) Nounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287 "L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing - Height Seated (Max) 0.079" (2.00mm) Lead Spacing Surface Purpose		
CategoryCapacitorsTantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TPECapacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Manufacturer Part Number	6TPE150MI
Initialum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TPECapacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.709" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Manufacturer	Panasonic Electronic Components
Package2917 (7343 Metric)SeriesPOSCAP? TPECapacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FeaturesDEFeaturesGeneral Purpose	Category	Capacitors
Series POSCAP? TPE Capacitance 150µF Tolerance ±20% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 18 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing - Features DE Features General Purpose		Tantalum - Polymer Capacitors
Capacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.709" (2.00mm)Lead Spacing52FeaturesDEFeaturesGeneral Purpose	Package	2917 (7343 Metric)
Tolerance±20%Voltage - Rated6.3VYopeMoldedESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FeaturesDEEFeaturesGeneral Purpose	Series	POSCAP? TPE
Voltage - RatedActivityVoltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Capacitance	150µF
TypeMoldedESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeDEFeaturesGeneral Purpose	Tolerance	±20%
AI8 mOhmESR (Equivalent Series Resistance)18 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Voltage - Rated	6.3V
Operating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Туре	Molded
Lifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	18 mOhm
Mounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Operating Temperature	-55°C ~ 105°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Lifetime @ Temp.	-
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Mounting Type	Surface Mount
Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeD2EFeaturesGeneral Purpose	Height - Seated (Max)	0.079" (2.00mm)
Features General Purpose	Lead Spacing	-
-	Manufacturer Size Code	D2E
Report errors?	Features	General Purpose
		Report errors?

6TPE150MI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

6TPE150MI Payment Methods



6TPE150MI Shipping Methods



If you have any question about 6TPE150MI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com