

70050K Information



For Reference Only

Part Number 70050K

Manufacturer Talema Group LLC

Category Transformers
Power Transformers

Description XFRMR TOROIDAL 15VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









70050K Specifications

Manufacturer Part Number 70050K Manufacturer Talema Group LLC Category Transformers Power Transformers Power Transformers Series 7XXXX Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 7V, Series 14V Current - Output (Max) Parallel 2.142A, Series 1.071A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)		
Category Transformers Package - Series 7XXXX Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 7V, Series 14V Current - Output (Max) Parallel 2.142A, Series 1.071A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)	Manufacturer Part Number	70050K
Package Series 7XXXX Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 7V, Series 14V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Weight Power - Insurance of Content of Cont	Manufacturer	Talema Group LLC
Package - TXXXX Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 7V, Series 14V Current - Output (Max) Parallel 2.142A, Series 1.071A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight	Category	Transformers
Series 7XXXX Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 7V, Series 14V Current - Output (Max) Parallel 2.142A, Series 1.071A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight		Power Transformers
Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 7V, Series 14V Current - Output (Max) Parallel 2.142A, Series 1.071A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight	Package	-
Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 7V, Series 14V Current - Output (Max) Parallel 2.142A, Series 1.071A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)	Series	7XXXX
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 2.142A, Series 1.071A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 7V, Series 14V Parallel 2.142A, Series 1.071A Parallel 7V, Series 14V Parallel 2.142A, Series 1.071A No Single, Multiple Taps No 26.00 40.00 40.00 Voltage - Isolation Voltage - Isolation Voltage - Isolation	Type	Toroidal
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 2.142A, Series 1.071A Dual Single, Multiple Taps No Power No No Power No No Power No	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual Single, Multiple Taps No Power No 15 VA Through Hole PC Pin 60.00mm L x 60.00mm W 26.30mm 4000Vrms Voltage - Isolation 4000Vrms Voltage - Isolation	Voltage - Secondary (Full Load)	Parallel 7V, Series 14V
Secondary Winding(s) Center Tap No Power - Max 15 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Single, Multiple Taps No 26.30M 4000Vrms 0.578 lb (262.18g)	Current - Output (Max)	Parallel 2.142A, Series 1.071A
Center TapNoPower - Max15 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension60.00mm L x 60.00mm WHeight - Seated (Max)26.30mmVoltage - Isolation4000VrmsWeight0.578 lb (262.18g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)	Secondary Winding(s)	Single, Multiple Taps
Mounting Type Through Hole PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)	Center Tap	No
Termination Style PC Pin Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)	Power - Max	15 VA
Size / Dimension 60.00mm L x 60.00mm W Height - Seated (Max) 26.30mm Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 26.30mm 4000Vrms 0.578 lb (262.18g)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 0.578 lb (262.18g)	Size / Dimension	60.00mm L x 60.00mm W
Weight 0.578 lb (262.18g)	Height - Seated (Max)	26.30mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	0.578 lb (262.18g)
		Report errors?

70050K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

70050K Payment Methods



















70050K Shipping Methods













If you have any question about 70050K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com