

7201SCWZBE

7201SCWZBE Information

	Heisener.com	Part Number Manufacturer Category Description Package	7201SCWZBE C&K Switches Toggle Switches SWITCH TOGGLE DPDT 0.4VA 20V - For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7201SCWZBE Specifications

Manufacturer Part Number 7201SCWZBE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection P67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000CircuitDPDTSwitch Function0.4VA (AC/DC)Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundIluminationNon-IluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Youting TypeSolder LugMounting TypeSolder LugIndender LugSolder LugFermination StyleSolder LugBushing Thread1/440Ingress ProtectionP67 - Dust Tight, WaterproofFeaturesExpose Color C	Manufacturer Part Number	7201SCWZBE
Toggle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Type10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/440Ingress ProtectionFoxy Sealed TerminalisFeaturesEpoxy Sealed Terminalis	Manufacturer	C&K
Package-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator Type040A (Acund RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Parel Mounting TypeSolder LugIndentify StafeSolder LugIndentify StafeSolder LugIndentify StafeSolder LugIndentify StafeSolder LugFernination Style1440Ingress ProtectionForsy Stafe	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular 6.55mm DiaBushing Thread14.40Ingress ProtectionFory Sealed TerminalsFeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Actuator StyleSolder LugPanel Cutout DimensionsGicrular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionFory Sealed TerminalsFeaturesEpsy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Type0.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionForsy Sealed TerminalsFeaturesEgoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpoxy Staled TerminalsFeaturesEpoxy Staled Terminals	Circuit	DPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Actuator Length	10.67mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7201SCWZBE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7201SCWZBE Payment Methods





If you have any question about 7201SCWZBE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com