

7205SDAGE

7205SDAGE Information

Contract terrice canto terre	Part Number Manufacturer Category Description Package	7205SDAGE C&K Switches Toggle Switches SWITCH TOGGLE DPDT 5A 120V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7205SDAGE Specifications

Manufacturer Part Number 7205SDAGE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function Mom-Off-Mom Current Rating SA (AC/DC) Voltage Rating - AC 28V Actuator Type Standard Round Actuator Length 12.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Actuator Length PC Pin Illumination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC28VVoltage Rating - DCSandard RoundActuator TypeSandard RoundIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage Nominal-Mouting TypePC PinInduning TypePC PinStandard Cound Fyned-Standard Syle-Standard Syle-St	Manufacturer Part Number	7205SDAGE
Toggle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCrcular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series7000CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length12.45mmIluminationNon-IlluminatedIlumination Type, Color-Mouting TypePanel Mount, Right AngleIlumination StylePanel Mount, Right AngleTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpsy Sealed Terminals	Category	Switches
Series7000CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC20VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length1.245mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Premination StylePen Mount, Right AnglePanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEposySealed Terminalis		Toggle Switches
CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fremination StylePonel Mount, Right AnglePanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleFermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionFoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	Mom-Off-Mom
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	12.45mm
Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount, Right Angle
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7205SDAGE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7205SDAGE Payment Methods Image: Im

If you have any question about 7205SDAGE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com