



7305TCWZQE Information

Heisener com

Part Number 7305TCWZQE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE 3PDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7305TCWZQE Specifications

Manufacturer Part Number 7305TCWZQE Manufacturer C&K Category Switches Package - Series 7000 Circuit 3PDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000Circuit3PDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7305TCWZQE
Package - 7000 Circuit 3PDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Momuning Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Peox Sealed Terminals	Manufacturer	C&K
Package - Series 7000 Circuit 3PDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Category	Switches
Series 7000 Circuit 3PDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals		Toggle Switches
Circuit3PDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals	Circuit	3PDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Features 120V 28V 28V 28V Actuator Length 17.45mm Non-Illumination Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 17.45mm Circular - 11.91mm Dia Dia Dia Dia Dia Dia Dia D	Switch Function	Mom-Off-Mom
Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Features Epoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Type, Color - Clumination Voltage (Nominal) - Mounting Type Panel Mount Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Actuator Length	17.45mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 11.91mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	15/32-32
	Ingress Protection	IP67 - Dust Tight, Waterproof
Donort orrong?	Features	Epoxy Sealed Terminals
Report errors?		Report errors?

7305TCWZQE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7305TCWZQE Payment Methods



















7305TCWZQE Shipping Methods













If you have any question about 7305TCWZQE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com