

7405MHZBE

7405MHZBE Information

Heisener.com	Part Number Manufacturer Category Description Package	7405MHZBE C&K Switches Toggle Switches SWITCH TOGGLE 4PDT 0.4VA 20V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7405MHZBE Specifications

Manufacturer Part Number 7405MHZBE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit 4PDT Switch Function Mon-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Illumination Non-Illuminated Illumination Sol8mm Illumination Type, Color - Termination Style Solder Lug Panel Cutout Dimensions Giclurar 6.35mm Dia Bushing Thread 1/440 Ingress Protection - Features Epoxy Sealed Terminals	• •	
CategorySwitchesToggle SwitchesPackage-Series7000Circuit4PDTSwitch FunctionMon-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundIluminationNon-IlluminatedIlumination Voltage (Nominal)-Ilumination Voltage (Nominal)Soler LugMounting TypeSider LugNonting TypeSider LugIngens ProtectionCircular 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7405MHZBE
Toggle SwitchesPackage-Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIluminationSolemantIlumination Type, Color-Mounting TypePanel MountPremination StyleSoler LugPanel Cutout DimensionsSoler LugBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminales	Category	Switches
Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StyleSolder LugPanel Cutout DimensionsGircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Treminals		Toggle Switches
Circuit4PDTSwitch FunctionMom-Off-MomCurrent RatingMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DCStandard RoundActuator TypeSomActuator LengthSomIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Scaled Terminals	Package	-
Switch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugIngens Protection14-40Ingers Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Panel MountSolder LugPanel MountSolder LugInder StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpsy Sealed TerminalsFeaturesEpsy Sealed Terminals	Circuit	4PDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length5.08mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutour DimensionsIcrular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpsy Sealed TerminalsFeaturesEpsy Sealed Terminals	Switch Function	Mom-Off-Mom
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Scaled Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	5.08mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7405MHZBE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7405MHZBE Payment Methods Image: Im

If you have any question about 7405MHZBE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com