

## 7405TZQE

lest a Quote

### 7405TZQE Information

Part Number	7405TZQE	
Manufacturer	C&K	
Category	Switches Toggle Switches	5
Description	SWITCH TOGGLE 4PDT 5A 120V	
Package	-	
	For the pricing/inventory/lead time, please contact	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	R
	Manufacturer Category Description	Manufacturer C&K   Category Switches Toggle Switches   Description SWITCH TOGGLE 4PDT 5A 120V   Package -   For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### 7405TZQE Specifications

ManufacturerC&KCategorySwitchesCategoryToggle SwitchesPackage-Package7000Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent Rating - AC5A (AC/DC)Voltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIluminationNon-IlluminatedIlumination Yoftage (Nominal)-Ilumination Voltage (Nominal)-		
CategorySwitchesPackage-Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundAltuator LengthNon-IlluminatedIlluminationSolerLugIllumination Voltage Nominal)-Mounting TypeSoler LugIndumination StyleSoler LugPanel Cutour DimensionsSoler LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Scaled Terminals	Manufacturer Part Number	7405TZQE
Toggle SwitchesPackage-Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSatndard RoundActuator TypeStandard RoundActuator LengthNon-IlluminatedIllumination-Illumination Type, Color-Mouting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminalis	Category	Switches
Series7000Circuit4PDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youring TypeSolder LugPanel Cutout DimensionsSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
Circuit4PDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator LengthI1.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel Cutout DimensionsSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress ProtectionEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	4PDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandar RoundActuator Type17.45mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugPanel Cutout Dimensions15/32-32Ingress Protection-FeaturesEpoxy Scaled Terminals	Switch Function	Mom-Off-Mom
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsIf S/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Type	Standard Round
Ilumination Type, Color-Ilumination Yoltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	17.45mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread15/32-32Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 11.91mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	15/32-32
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### 7405TZQE Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 7405TZQE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com