



7408SYWQE Information

Heisener.com

Part Number 7408SYWQE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE 4PDT 5A 120V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7408SYWQE Specifications

Manufacturer Part Number 7408SYWQE Manufacturer C&K Category Switches Package - Series 7000 Circuit 4PDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
Category Switches Package - Series 7000 Circuit 4PDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer Part Number	7408SYWQE
Package - Series 7000 Circuit 4PDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer	C&K
Package - Series 7000 Circuit 4PDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 7000 Circuit 4PDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
Circuit4PDTSwitch FunctionOn-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	4PDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Mom
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	10.67mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Wire Wrap
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7408SYWQE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7408SYWQE Payment Methods



















7408SYWQE Shipping Methods













If you have any question about 7408SYWQE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com