

7760056057 Information

Manufact
Category

Part Number 7760056057 Manufacturer Weidmuller Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 115V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7760056057 Specifications

Manufacturer Part Number Manufacturer Weidmuller Relays Power Relays, Over 2 Amps Package Series DRM Relay Type General Purpose Coil Current 10.8mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Relays Package 7- 7- 7- 7- 7- 7- 8- 8- Mounting Type Socketable Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesDRMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.8mACoil Voltage115VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	7760056057
Package - Series DRM Relay Type General Purpose Coil Type Non Latching Coil Current 10.8mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	Weidmuller
Package - DRM Relay Type General Purpose Coil Type Non Latching Coil Current 10.8mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesDRMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.8mACoil Voltage115VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 10.8mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Package	-
Coil TypeNon LatchingCoil Current10.8mACoil Voltage115VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	DRM
Coil Current 10.8mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	10.8mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Coil Voltage	115VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC - Max
Operate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	92 VAC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	34.5 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
D (0	Termination Style	Plug In
Report errors?		Report errors?

7760056057 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7760056057 Payment Methods





















7760056057 Shipping Methods













If you have any question about 7760056057, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com