

7W25000105 Information



For Reference Only

Part Number 7W25000105

Manufacturer TXC CORPORATION

Category Crystals, Oscillators, Resonators

Oscillators

Description OSC XO 25MHZ 2.5V SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7W25000105 Specifications

Manufacturer Part Number 7W25000105 Manufacturer TXC CORPORATION Category Crystals, Oscillators, Resonators Oscillators A-SMD, No Lead Series 7W Type XO (Standard) Frequency 25MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)			
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 7W Type XO (Standard) Frequency 25MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Manufacturer Part Number	7W25000105	
Package 4-SMD, No Lead Series 7W Type XO (Standard) Frequency 25MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Manufacturer	TXC CORPORATION	
Package 4-SMD, No Lead Series 7W Type XO (Standard) Frequency 25MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Category	Crystals, Oscillators, Resonators	
Series 7W Type XO (Standard) Frequency 25MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)		Oscillators	
Type XO (Standard) Frequency 25MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Package	4-SMD, No Lead	
Frequency 25MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Series	7W	
Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Туре	XO (Standard)	
Output CMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Frequency	25MHz	
Voltage - Supply Erequency Stability Operating Temperature -40°C ~ 85°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max)	Function	Enable/Disable	
Frequency Stability $\pm 50 \mathrm{ppm}$ Operating Temperature $-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$ Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD , No Lead Size / Dimension $0.276^{\circ}\mathrm{L} \times 0.197^{\circ}\mathrm{W} \ (7.00 \mathrm{mm} \times 5.00 \mathrm{mm})$ Height - Seated (Max) $0.056^{\circ}\mathrm{W} \ (1.42 \mathrm{mm})$	Output	CMOS	
Operating Temperature -40°C ~ 85°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Voltage - Supply	2.5V	
Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Frequency Stability	±50ppm	
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Operating Temperature	-40°C ~ 85°C	
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Current - Supply (Max)	-	
Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Ratings	-	
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.056" (1.42mm)	Mounting Type	Surface Mount	
Height - Seated (Max) 0.056" (1.42mm)	Package / Case	4-SMD, No Lead	
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)	
Report errors?	Height - Seated (Max)	0.056" (1.42mm)	
1		Report erro	rs?

7W25000105 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7W25000105 Payment Methods





















7W25000105 Shipping Methods













If you have any question about 7W25000105, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com