

9011-05-10

9011-05-10 Information



Part Number	9011-05-10	
Manufacturer	Coto Technology	
Category	Relays Signal Relays, Up to 2 Amps	
Description	RELAY REED SPST 250MA 5V	
Package	-	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



9011-05-10 Specifications

Manufacturer Part Number9011-05-10Manufacturer CCoto TechnologyCategoryRelaysPackage-Package-Series9011Relay TypeReedCoil TypeNon LatchingCoil Current10mACottact FormSPST-NO (I Form A)Contact Rating (Current)375 VDCSwitching Voltage (Max)3.75 VDCTurn On Voltage (Max)0.4 VDCTurn Of Voltage (Max)0.1 msRelease Time0.1 msFeaturesMagnetic ShieldMounting TypeFriorgh HoleComposition StylePC Pin		
CategoryRelaysSagnal Relays, Up to 2 AmpsPackagePackageSeries9011Relay TypeRedCoil TypeCoil CurrentCoil CurrentContact FormSortact Rating (Current)Switching VoltageSwitching VoltageSwitching Voltage (Max)Turn On Voltage (Max)Qierate TimeOperate TimeRelease TimeFeaturesMounting TypeTermination StylePromination StylePromination StylePromination StylePartice StatePromination StylePartice StatePartice State <td>Manufacturer Part Number</td> <td>9011-05-10</td>	Manufacturer Part Number	9011-05-10
Signal Relays, Up to 2 AmpsPackage-Series9011Relay TypeReedCoil TypeNon LatchingCoil Current10mAColl VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.75 VDCOperate Time0.4 VDCOperate Time0.1msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Coto Technology
Package-Series9011Relay TypeReedCoil TypeNon LatchingCoil Current10mACoil VoltageSVDCContact FormSPST-NO(1 Form A)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Man)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFaturesMagnetic ShieldMounting TypeCong HoleTermination StylePC Pin	Category	Relays
Series9011Relay TypeReedCoil TypeNon LatchingCoil Current10mACoil VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.1msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeCP inTermination StylePC in		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current10mACoil Olage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Man)3.75 VDCOperate Time0.4 VDCRelase Time0.1msFeaturesMagnetic ShieldMounting TypeTrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LachingCoil Current10mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.75 VDCCurrent Finne0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeConstantFentination StyleConstantCo	Series	9011
Coil Current10mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeFC Pin	Relay Type	Reed
Coil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Form250mAContact Rating (Current)200VAC, 100VDC - MaxSwitching Voltage (Max)3.75 VDCTurn On Voltage (Max)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Coil Current	10mA
Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Coil Voltage	5VDC
Switching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	250mA
Turn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	100VAC, 100VDC - Max
Operate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.75 VDC
Release Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	0.4 VDC
FeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Operate Time	0.35ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	0.1ms
Termination Style PC Pin	Features	Magnetic Shield
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

9011-05-10 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 9011-05-10, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com