



ACB40DYRR Information

Heisener.com

Part Number ACB40DYRR

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 80POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACB40DYRR Specifications

Manufacturer Part Number ACB40DYRR Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Teb-tob T KK Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~150°C	Manufacturer Part Number	ACB40DYRR
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions Bay/Row 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	40
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	80
Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	Board Lock, Card Extender
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Board Edge, Straddle Mount
Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Color Black Flange Feature Operating Temperature Sor C ~ 150°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Cantilever Color Black Flange Feature - Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Color Black Flange Feature -65°C ~ 150°C	Contact Finish	Gold
Color Black Flange Feature -65°C ~ 150°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Operating Temperature -65°C ~ 150°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ACB40DYRR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACB40DYRR Payment Methods



















ACB40DYRR Shipping Methods













If you have any question about ACB40DYRR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com