



Heisener.com

ACC06E-14S-2S(003)(A24) Information

Part Number ACC06E-14S-2S(003)(A24) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 4POS STRAIGHT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACC06E-14S-2S(003)(A24) Specifications

Manufacturer Part Number ACC06E-14S-2S(003)(A24) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer Part Number	ACC06E-14S-2S(003)(A24)
Circular Connectors Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating - Circular Connectors AC, MIL-5015 Derivative AC, M	Manufacturer	Amphenol Industrial Operations
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Category	Connectors, Interconnects
Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Series	AC, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating -	Number of Positions	4
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Shell Size - Insert	14S-2
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Mounting Hardware, Strain Relief	Orientation	N (Normal)
Contact Finish Gold Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Ingress Protection	Environment Resistant
Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	Mounting Hardware, Strain Relief
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

ACC06E-14S-2S(003)(A24) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACC06E-14S-2S(003)(A24) Payment Methods



















ACC06E-14S-2S(003)(A24) Shipping Methods













If you have any question about ACC06E-14S-2S(003)(A24), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com