



Heisener.com

ACS06F-28-16SB(003) Information

Part Number ACS06F-28-16SB(003)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 20POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACS06F-28-16SB(003) Specifications

Manufacturer Part Number ACS06F-28-16SB(003) Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series AC-B, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 20 Shell Size - Insert 28-16 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesAC-B, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	ACS06F-28-16SB(003)
Package-SeriesAC-B, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - AC-B, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 20 Shell Size - Insert 28-16 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Category	Connectors, Interconnects
Series AC-B, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 20 Shell Size - Insert 28-16 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	AC-B, MIL-5015 Derivative
Shell Size - Insert 28-16 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Number of Positions	20
Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	28-16
Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	N (Normal)
Contact Finish Features Strain Relief Voltage - Rated Current Rating Silver Strain Relief	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
1		Report errors?

ACS06F-28-16SB(003) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACS06F-28-16SB(003) Payment Methods



















ACS06F-28-16SB(003) Shipping Methods













If you have any question about ACS06F-28-16SB(003), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com