

AD1120-48F Information

Heisener.com

Part Number AD1120-48F

Manufacturer ATOP Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description 120W/2.5A DIN-RAIL 48VDC POWER S

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AD1120-48F Specifications

Manufacturer Part Number AD1120-48F Manufacturer ATOP Technologies Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Manufacturer Part Number	AD1120-48F
Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Manufacturer	ATOP Technologies
Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Package	-
Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Series	-
Voltage - Input 100 ~ 240 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Туре	Enclosed
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension - Current - Output (Max) - 2.5A Power (Watts) 120W ITE (Commercial) - Commercial) - Commercial -	Voltage - Input	100 ~ 240 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension - Control of L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension - 2.5A 120W 82W 120W 82W 120W 120W	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 2.5A 2.5A 2.0W ITE (Commercial)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 120W ITE (Commercial) Adjustable Output Adjustable Ou	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Current - Output (Max)	2.5A
Voltage - Isolation Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Power (Watts)	120W
Efficiency 82% Operating Temperature -20°C ~ 50°C Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Applications	ITE (Commercial)
Operating Temperature -20°C ~ 50°C Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Voltage - Isolation	-
Features Adjustable Output, DC Input Capable Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Efficiency	82%
Mounting Type DIN Rail Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Operating Temperature	-20°C ~ 50°C
Size / Dimension 4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)	Features	Adjustable Output, DC Input Capable
	Mounting Type	DIN Rail
Report errors?	Size / Dimension	4.76" L x 2.95" W x 4.33" H (121.0mm x 75.0mm x 110.0mm)
		Report errors?

AD1120-48F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AD1120-48F Payment Methods



















AD1120-48F Shipping Methods













If you have any question about AD1120-48F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com