



### **ADUM3400CRWZ Information**



For Reference Only

Part Number ADUM3400CRWZ
Manufacturer Analog Devices Inc.

**Category** Isolators

**Digital Isolators** 

**Description** DGTL ISO 2.5KV GEN PURP 16SOIC **Package** 16-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ADUM3400CRWZ Specifications**

Manufacturer Part Number         ADUM3400CRWZ           Manufacturer         Analog Devices Inc.           Category         Isolators           Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         4/0           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         90Mbps           Propagation Delay tpLH / tpHL (Max)         32ns, 32ns           Pulse Width Distortion (Max)         2ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC (0.295", 7.50mm Width)		
Category         Isolators           Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         4/0           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         90Mbps           Propagation Delay tpLH / tpHL (Max)         32ns, 32ns           Pulse Width Distortion (Max)         2ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC	Manufacturer Part Number	ADUM3400CRWZ
Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         4/0           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         90Mbps           Propagation Delay tpLH / tpHL (Max)         32ns, 32ns           Pulse Width Distortion (Max)         2ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC	Manufacturer	Analog Devices Inc.
Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         4/0           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         90Mbps           Propagation Delay tpLH / tpHL (Max)         32ns, 32ns           Pulse Width Distortion (Max)         2ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC	Category	Isolators
Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         4/0           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         90Mbps           Propagation Delay tpLH / tpHL (Max)         32ns, 32ns           Pulse Width Distortion (Max)         2ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC		Digital Isolators
Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         4/0           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         90Mbps           Propagation Delay tpLH / tpHL (Max)         32ns, 32ns           Pulse Width Distortion (Max)         2ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC	Package	16-SOIC (0.295", 7.50mm Width)
Type General Purpose  Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 90Mbps Propagation Delay tpLH / tpHL (Max) 32ns, 32ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Series	iCoupler?
Isolated Power  Number of Channels  4 Inputs - Side 1/Side 2  4/0  Channel Type  Unidirectional  Voltage - Isolation  2500Vrms  Common Mode Transient Immunity (Min)  25kV/µs  Data Rate  90Mbps  Propagation Delay tpLH / tpHL (Max)  32ns, 32ns  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Technology	Magnetic Coupling
Number of Channels4Inputs - Side 1/Side 24/0Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate90MbpsPropagation Delay tpLH / tpHL (Max)32ns, 32nsPulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Type	General Purpose
Inputs - Side 1/Side 2  Channel Type  Unidirectional  Voltage - Isolation  2500Vrms  Common Mode Transient Immunity (Min)  Data Rate  90Mbps  Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Isolated Power	No
Channel Type Voltage - Isolation 2500Vrms  Common Mode Transient Immunity (Min) 25kV/µs  Data Rate 90Mbps  Propagation Delay tpLH / tpHL (Max) 2sns  Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 3 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Number of Channels	4
Voltage - Isolation  2500Vrms  Common Mode Transient Immunity (Min)  25kV/µs  Data Rate  90Mbps  Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Inputs - Side 1/Side 2	4/0
Common Mode Transient Immunity (Min)  Data Rate  90Mbps  Propagation Delay tpLH / tpHL (Max)  21s  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Channel Type	Unidirectional
Data Rate90MbpsPropagation Delay tpLH / tpHL (Max)32ns, 32nsPulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Voltage - Isolation	2500Vrms
Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Common Mode Transient Immunity (Min)	$25kV/\mu s$
Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Data Rate	90Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $3 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC}$ ( $0.295^{\circ}$ , $7.50 \text{mm}$ Width)Supplier Device Package $16\text{-SOIC}$	Propagation Delay tpLH / tpHL (Max)	32ns, 32ns
Voltage - Supply $3\ V \sim 5.5\ V$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC}\ (0.295'', 7.50\text{mm Width})$ Supplier Device Package $16\text{-SOIC}$	Pulse Width Distortion (Max)	2ns
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC}$ (0.295", 7.50mm Width) Supplier Device Package $16\text{-SOIC}$	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Voltage - Supply	3 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 105°C
	Package / Case	16-SOIC (0.295", 7.50mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

### **ADUM3400CRWZ Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ADUM3400CRWZ Payment Methods**



















# **ADUM3400CRWZ Shipping Methods**













If you have any question about ADUM3400CRWZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com