



AF162-JR-0715KL Information



For Reference Only

Part Number AF162-JR-0715KL

Manufacturer Yageo **Category** Resistors

Resistor Networks, Arrays

Description RES ARRAY 2 RES 15K OHM 0606

Package 0606, Convex

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AF162-JR-0715KL Specifications

| Manufacturer AF162-JR-0715KL Manufacturer Yageo Category Resistors Resistor Networks, Arrays Package 0606, Convex Series AF162 Circuit Type Isolated Resistance (Ohms) 15k Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | | |
|---|--------------------------|---------------------------------------|
| Category Resistors Package 0606, Convex Series AF162 Circuit Type Isolated Resistance (Ohms) 15k Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Manufacturer Part Number | AF162-JR-0715KL |
| Resistor Networks, Arrays Package 0606, Convex Series AF162 Circuit Type Isolated Resistance (Ohms) 15k Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Manufacturer | Yageo |
| Package 0606, Convex Series AF162 Circuit Type Isolated Resistance (Ohms) 15k Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Category | Resistors |
| Series AF162 Circuit Type Isolated Resistance (Ohms) 15k Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | | Resistor Networks, Arrays |
| Circuit Type Isolated Resistance (Ohms) 15k Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Package | 0606, Convex |
| Resistance (Ohms) 15k Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Series | AF162 |
| Tolerance ±5% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Circuit Type | Isolated |
| Number of Resistors2Number of Pins4Power Per Element62.5mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case0606, ConvexSupplier Device Package0606Size / Dimension0.063" L x 0.063" W (1.60mm x 1.60mm)Height - Seated (Max)0.020" (0.50mm) | Resistance (Ohms) | 15k |
| Number of Pins Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Tolerance | ±5% |
| Power Per Element 62.5mW Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ ApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case 0606 , ConvexSupplier Device Package 0606 Size / Dimension $0.063^{\circ}\text{L} \times 0.063^{\circ}\text{W} (1.60 \text{mm} \times 1.60 \text{mm})$ Height - Seated (Max) 0.020° (0.50 mm) | Number of Resistors | 2 |
| Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Number of Pins | 4 |
| Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Power Per Element | 62.5mW |
| Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Temperature Coefficient | ±200ppm/°C |
| Mounting Type Surface Mount Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Operating Temperature | -55°C ~ 155°C |
| Package / Case 0606, Convex Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Applications | DDRAM, SDRAM |
| Supplier Device Package 0606 Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Mounting Type | Surface Mount |
| Size / Dimension 0.063" L x 0.063" W (1.60mm x 1.60mm) Height - Seated (Max) 0.020" (0.50mm) | Package / Case | 0606, Convex |
| Height - Seated (Max) 0.020" (0.50mm) | Supplier Device Package | 0606 |
| | Size / Dimension | 0.063" L x 0.063" W (1.60mm x 1.60mm) |
| Report errors? | Height - Seated (Max) | 0.020" (0.50mm) |
| | | Report errors? |

AF162-JR-0715KL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AF162-JR-0715KL Payment Methods



















AF162-JR-0715KL Shipping Methods













If you have any question about AF162-JR-0715KL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com