



AHM85PS24C2-8 Information



For Reference Only

Part Number AHM85PS24C2-8

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 85W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AHM85PS24C2-8 Specifications

Manufacturer Part Number AHM85PS24C2-8 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series AHM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series AHM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Manufacturer Part Number	AHM85PS24C2-8
Package - Series AHM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Manufacturer	XP Power
Package - Series AHM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesAHMRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output24VCurrent - Output (Max)3.54APower (Watts)85WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output24VCurrent - Output (Max)3.54APower (Watts)85WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Series	AHM
Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Region Utilized	International
Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $5.90^{\circ}\text{L x } 2.52^{\circ}\text{W x } 1.45^{\circ}\text{H } (150.0\text{mm x } 64.0\text{mm x } 37.0\text{mm})$	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption Folarization Applications ITE (Commercial), Medical Efficiency Operating Temperature O°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 24V 3.54A 85W Row (Max) Folarization - UTE (Commercial), Medical Evel V Operating Temperature O°C ~ 60°C Output Connector Power DIN, 4 Pin 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 3.54A 85W 85W Comwercial), Medical Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Voltage - Input	80 ~ 264 VAC
Power (Watts) 85W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Voltage - Output	24V
No Load Power Consumption 500mW (Max) Polarization - ITE (Commercial), Medical Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Current - Output (Max)	3.54A
Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Power (Watts)	85W
Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $5.90^{\circ}\text{L x } 2.52^{\circ}\text{W x } 1.45^{\circ}\text{H } (150.0\text{mm x } 64.0\text{mm x } 37.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $5.90^{\circ}\text{L x } 2.52^{\circ}\text{W x } 1.45^{\circ}\text{H } (150.0\text{mm x } 64.0\text{mm x } 37.0\text{mm})$	Applications	ITE (Commercial), Medical
Output Connector Power DIN, 4 Pin Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Efficiency	Level V
Size / Dimension 5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	5.90" L x 2.52" W x 1.45" H (150.0mm x 64.0mm x 37.0mm)
		Report errors?

AHM85PS24C2-8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AHM85PS24C2-8 Payment Methods



















AHM85PS24C2-8 Shipping Methods













If you have any question about AHM85PS24C2-8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com