



ALE13F06 Information



For Reference Only

Part Number ALE13F06

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALE13F06 Specifications

Manufacturer Part Number ALE13F06 Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm) REPORT errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.3 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	ALE13F06
Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer	Panasonic Electric Works
Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.3 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Release Time 1 Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Package	-
Coil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.3 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Series	ALE
Coil Current Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style 66.7mA 6	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Release Time 1 Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Current	66.7mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Voltage	6VDC
Switching Voltage Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style 277VAC - Max 4.5 VDC 0.3 VDC 10ms 1	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Switching Voltage	277VAC - Max
Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	4.5 VDC
Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	0.3 VDC
Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Release Time	20ms
Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Features	Insulation - Class F
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.187" (4.7mm)
		Report errors?

ALE13F06 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALE13F06 Payment Methods





















ALE13F06 Shipping Methods













If you have any question about ALE13F06, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com