



ALE1PF05 Information



For Reference Only

Part Number ALE1PF05

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALE1PF05 Specifications

| Manufacturer Part NumberALE1PF05ManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin | | |
|---|--------------------------|---------------------------|
| CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin | Manufacturer Part Number | ALE1PF05 |
| Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style Purpose | Manufacturer | Panasonic Electric Works |
| Package-SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin | Category | Relays |
| SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin | | Power Relays, Over 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin | Package | - |
| Coil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin | Series | ALE |
| Coil Current 80mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin | Relay Type | General Purpose |
| Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin | Coil Type | Non Latching |
| Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin | Coil Current | 80mA |
| Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style | Coil Voltage | 5VDC |
| Switching Voltage 277VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin | Contact Form | SPST-NO (1 Form A) |
| Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style 3.75 VDC 1.25 VDC 1.26 VDC 1.27 VDC 1.28 VDC 1.29 VDC 1.29 VDC 1.29 VDC 1.29 VDC 1.20 VDC | Contact Rating (Current) | 16A |
| Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style O.25 VDC Toms POPIN | Switching Voltage | 277VAC - Max |
| Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin | Turn On Voltage (Max) | 3.75 VDC |
| Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin | Turn Off Voltage (Min) | 0.25 VDC |
| Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin | Operate Time | 20ms |
| Mounting Type Through Hole Termination Style PC Pin | Release Time | 20ms |
| Termination Style PC Pin | Features | Insulation - Class F |
| · | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

ALE1PF05 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALE1PF05 Payment Methods



















ALE1PF05 Shipping Methods













If you have any question about ALE1PF05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com