

AMC65DRTI

AMC65DRTI Information

Heisener.com	 AMC65DRTI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 130POS .100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AMC65DRTI Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeGuidContact TypeGuidContact TypeGuidContact TypeSolderContact TypeFull BellowsContact TypeGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65% ~ 150°C	Manufacturer Part Number	AMC65DRTI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeGoldContact TypeTuro GreenFlange Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeGreenFlange Feature-50°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSupin (0.76µm)Contact TypeFeallellowsContact TypeGoldContact TypeSupin (0.76µm)Contact TypeFeallellowsContact TypeGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-Solce Carlos C	Package	-
GenderFemaleNumber of Positions/Bay/Row65Number of Positions130Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperatureo.5°C ~ 150°C	Series	-
Number of Positions/Bay/Row65Number of Positions130Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeSupin (0.76µm)ColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 130 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	65
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C	Number of Positions	130
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature-55°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
ColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

AMC65DRTI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AMC65DRTI Payment Methods



AMC65DRTI Shipping Methods



If you have any question about AMC65DRTI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com