



ARN30A24X Information

Heisener.com

Part Number ARN30A24X

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY RF SPDT 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ARN30A24X Specifications

Manufacturer Part NumberARN30A24XManufacturerPanasonic Electric WorksCategoryRelaysBackage-SeriesARNRelay TypeRFCoil TypeNon LatchingCoil Current13.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeSurface Mount		
Category Relays Signal Relays, Up to 2 Amps Package - Series ARN Relay Type RF Coil Type Non Latching Coil Current 13.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Sealed - Flux Protection	Manufacturer Part Number	ARN30A24X
Package - Series ARN Relay Type RF Coil Type Non Latching Coil Current 13.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) - Switching Voltage - Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms Features Sealed - Flux Protection	Manufacturer	Panasonic Electric Works
Package - Series ARN Relay Type RF Coil Type Non Latching Coil Current 13.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) - Switching Voltage - Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms Features Sealed - Flux Protection	Category	Relays
SeriesARNRelay TypeRFCoil TypeNon LatchingCoil Current13.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux Protection		Signal Relays, Up to 2 Amps
Relay Type RF Coil Type Non Latching Coil Current 13.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) - Switching Voltage - Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms Features Sealed - Flux Protection	Package	-
Coil TypeNon LatchingCoil Current13.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux Protection	Series	ARN
Coil Current13.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux Protection	Relay Type	RF
Coil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux Protection	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms Features Sealed - Flux Protection	Coil Current	13.3mA
Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time Sms Release Time 5ms Features Sealed - Flux Protection	Coil Voltage	24VDC
Switching Voltage Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms Features Sealed - Flux Protection	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features Sealed - Flux Protection	Contact Rating (Current)	-
Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features Sealed - Flux Protection	Switching Voltage	-
Operate Time5msRelease Time5msFeaturesSealed - Flux Protection	Turn On Voltage (Max)	18 VDC
Release Time5msFeaturesSealed - Flux Protection	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Flux Protection	Operate Time	5ms
	Release Time	5ms
Mounting Type Surface Mount	Features	Sealed - Flux Protection
	Mounting Type	Surface Mount
Termination Style Gull Wing	Termination Style	Gull Wing
Report errors?		Report errors?

ARN30A24X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ARN30A24X Payment Methods



















ARN30A24X Shipping Methods













If you have any question about ARN30A24X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com