

B41042A5476M Information

Heisener.com

For Reference Only

Category

Part Number B41042A5476M Manufacturer EPCOS (TDK) Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 25V RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41042A5476M Specifications

Manufacturer Part Number B41042A5476M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41042 Capacitance 47μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 148.4mA @ 120Hz Ripple Current - High Frequency 212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	1	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41042 Capacitance 47µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 148.4mA @ 120Hz Ripple Current - High Frequency 1212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Tabelage Capacitors Radial, Can R	Manufacturer Part Number	B41042A5476M
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41042Capacitance47μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency148.4mA @ 120HzRipple Current - High Frequency212m @ 100kHzImpedance1.2 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41042Capacitance47µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency148.4mA @ 120HzRipple Current - High Frequency212mA @ 100kHzImpedance1.2 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesB41042Capacitance47μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency148.4mA @ 120HzRipple Current - High Frequency212mA @ 100kHzImpedance1.2 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance 47µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 148.4mA @ 120Hz Ripple Current - High Frequency 212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 148.4mA @ 120Hz Ripple Current - High Frequency 212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole	Series	B41042
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 105°C - Conneal Purpose General Purpose 148.4mA @ 120Hz 212mA @ 100kHz 1.2 Ohms 0.098" (2.50mm) 0.248" Dia (6.30mm) 0.492" (12.50mm) Through Hole	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 148.4mA @ 120Hz Ripple Current - High Frequency 212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 148.4mA @ 120Hz Ripple Current - High Frequency 1212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 105°C 6105°C 6206 6207 6207 6208	Voltage - Rated	25V
Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar General Purpose 148.4mA @ 120Hz 212mA @ 100kHz 1.2 Ohms 0.098" (2.50mm) 0.248" Dia (6.30mm) 0.492" (12.50mm) Through Hole	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 148.4mA @ 120Hz 212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 212mA @ 100kHz Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance 1.2 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 212mA @ 100kHz 1.2 Ohms 0.492" (2.50mm) Through Hole	Applications	General Purpose
Impedance1.2 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	148.4mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	212mA @ 100kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	1.2 Ohms
Height - Seated (Max) Surface Mount Land Size Mounting Type O.492" (12.50mm) - Through Hole	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole	Height - Seated (Max)	0.492" (12.50mm)
	Surface Mount Land Size	-
Package / Case Radial, Can	Mounting Type	Through Hole
,	Package / Case	Radial, Can
Report errors?		Report errors?

B41042A5476M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41042A5476M Payment Methods



















B41042A5476M Shipping Methods













If you have any question about B41042A5476M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com