



B41858C3228M8 Information

Heisener.com

Part Number B41858C3228M8
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2200UF 20% 10V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41858C3228M8 Specifications

Manufacturer Part NumberB41858C3228M8ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, CanSeriesB41858Capacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)62 mOhm @ 10kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency1.396A @ 100kHzImpedance60 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41858 Capacitance 2200µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 62 mOhm @ 10kHz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polar Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Manufacturer Part Number	B41858C3228M8
PackageRadial, CanSeriesB41858Capacitance2200μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)62 mOhm @ 10kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency1.396A @ 100kHzImpedance60 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41858Capacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)62 mOhm @ 10kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency1.396A @ 100kHzImpedance60 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-	Category	Capacitors
Series B41858 Capacitance 2200µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 62 mOhm @ 10kHz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 2200μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 62 mOhm @ 10kHz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Package	Radial, Can
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 62 mOhm @ 10kHz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Series	B41858
Voltage - Rated ESR (Equivalent Series Resistance) 62 mOhm @ 10kHz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 512e / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size 10V 62 mOhm @ 10kHz 63 mOhms 1.396A @ 100kHz 64 mOhms 1.396A @ 100kHz	Capacitance	2200μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Voltage - Rated	10V
Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size -55°C ~ 105°C Automotive Automotive 6 mOhms 1.396A @ 100kHz 60 mOhms 0.197" (5.00mm) 0.866" (22.00mm)	ESR (Equivalent Series Resistance)	62 mOhm @ 10kHz
Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Inspedance Lead Spacing Current - Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Automotive Automotive 1.396A @ 100kHz 1.396A @ 100kHz 60 mOhms 60 mOhms 0.492" Dia (12.50mm) 0.492" Dia (12.50mm) -	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency - 1.396A @ 100kHz Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Applications	Automotive
Impedance 60 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	-
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	1.396A @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-	Impedance	60 mOhms
Height - Seated (Max) Surface Mount Land Size 0.866" (22.00mm) -	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size -	Size / Dimension	0.492" Dia (12.50mm)
	Height - Seated (Max)	0.866" (22.00mm)
Mounting Type Through Hole	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

B41858C3228M8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41858C3228M8 Payment Methods



















B41858C3228M8 Shipping Methods













If you have any question about B41858C3228M8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com