

B43041A2335M

Request a Quote

B43041A2335M Information

Part Number	B43041A2335M	
Manufacturer	EPCOS (TDK)	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	Description CAP ALUM 3.3UF 20% 200V RADIAL	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact	
For Reference Only	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	
	Manufacturer Category Description	Aluminum Electrolytic Capacitors Description CAP ALUM 3.3UF 20% 200V RADIAL Package Radial, Can For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43041A2335M Specifications

ManufacturerEPCOS (TDK)CatagoryCapacitorsPackageAtuminum Electrolytic CapacitorsPackageRadial, CanSeriesB43041Capacitance3.3µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB43041Capacitance3.3µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Manufacturer Part Number	B43041A2335M
Adminum Electrolytic CapacitorsPackageRadial, CanSeriesB43041Capacitance3.3μFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency12mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.98" (2.50mm)Size / Dimension0.442" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43041Capacitance3.3µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency30mA @ 100kHzRiple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.442" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesB43041Capacitance3.3μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance3.3µFColorance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Polaring TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarrPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	B43041
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.442" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Capacitance	3.3µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pounting TypeFrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency12mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	12mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	30mA @ 100kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
1		Report errors?

B43041A2335M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43041A2335M Payment Methods





If you have any question about B43041A2335M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com