

B43231A6277M

Request a Quote

B43231A6277M Information

	Part Number	B43231A6277M
	Manufacturer	EPCOS (TDK)
www.heisener.com	Category	Capacitors Aluminum Electrolytic Capacitors
-/2	Description	CAP ALUM 270UF 20% 500V SNAP
6	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43231A6277M Specifications

Manufacturer Part NumberB43231A6277MManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43231Capacitance270µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeApplications1.45A @ 120HzRipple Current - Low Frequency.Impedance.Lead Spacing0.394" (10.0mm)Size / Dimension1.350" (47.00mm)Height - Seated (Max).Surface Mount Land Size.	
CategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43231Capacitance270µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43231Capacitance270μFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
PackageRadial, Can - Snap-InSeriesB43231Capacitance270μFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature2000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzImpedance-Lad Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)1.850" (47.00mm)	
SeriesB43231Capacitance270μFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency2.248A @ 20kHzImpedance-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Capacitance270µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature>25°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzInpedance>Lead Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Kirghe Munt Land Size>Surface Mount Land Size>	
Tolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
ESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency2.248A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency2.248A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Operating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency2.248A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency2.248A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
ApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency2.248A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Ripple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency2.248A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
In a constraint of the product of t	
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	
Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In	
Repor	t errors?

B43231A6277M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43231A6277M Payment Methods



B43231A6277M Shipping Methods



If you have any question about B43231A6277M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com