

B43305A2188M60

lest a Quote

B43305A2188M60 Information

Heisener.com	Part Number	B43305A2188M60	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 1800UF 20% 200V SNAP	- 33
	Package	Radial, Can - Snap-In	- 22
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Requ

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305A2188M60 Specifications

Manufacturer Part NumberB43305A2188M60ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43305CapacitanceB43305Capacitance1800µFTolerance200%Voltage - Rated2000 Mrs @ 85°COperating Temperature40°C ~ 85°COperating Temperature60an MinusApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency0.394° (10.00mm)Size / Dimension1.181° Dia (30.00mm)Size / Dimension1.850° (47.00mm)Gurface Mount Land Size-Mounting TypeThrough HoleSurface Mount Land Size-Mounting TypeThrough HolePacemeter-	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance100 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFinogatical FinogaticalPackage / CaseRatial, Can - Snap-In	Manufacturer Part Number	B43305A2188M60
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43305Capacitance1800μFTolerance-20%Voltage - Rated00VESR (Equivalent Series Resistance)00 nOhm @ 100HzDerating Temper0000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hogh Frequency3.87A @ 100HzRipple Current - High Frequency0.394" (1.00mm)Lead Spacing0.394" (1.00mm)Size / Dimension1.181" Dia (3.00mm)Hight - Seated (Max).Surface Mount Land Size-Houning TypeMouning TypePackage / CaseMail Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance1800µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)70 mOhm @ 100HzDerating Temperature2000 Hrs @ 85°COparating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFincugationPackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency3.87A @ 100HzInpedance1.00 mOhmsSize / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1800μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzInpedance100 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia (Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzImpedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated200VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzImpedance100 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Capacitance	1800µF
C70 mOhm @ 100HzESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	70 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)3.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40° C ~ 85° C
Ripple Current - Low Frequency3.87A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3.87A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	100 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report erro	Package / Case	Radial, Can - Snap-In
Report circ		Report errors?

B43305A2188M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305A2188M60 Payment Methods





If you have any question about B43305A2188M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com