



B43305B5127M82 Information

Manufact Category Heisener.com

Part Number B43305B5127M82
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 120UF 20% 450V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43305B5127M82 Specifications

Manufacturer Part Number B43305B5127M82 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 120μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 1.13 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 970mA @ 100Hz	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 120µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Capacitors Radial, Can - Snap-In - 3 Lead 84305 120µF 120µF 120% 450V 20% 450V Capacitors Polar 120µF 1.13 Ohm @ 100Hz 1.13 Ohm @ 100Hz 2000 Hrs @ 85°C General Purpose	Manufacturer Part Number	B43305B5127M82
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 120μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency 970mA @ 100Hz	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance $120\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance) $1.13 \text{ Ohm } @ 100\text{Hz}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $970\text{mA} @ 100\text{Hz}$	Category	Capacitors
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		Aluminum Electrolytic Capacitors
Capacitance $120\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance) $1.13 \text{ Ohm } @ 100\text{Hz}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $970\text{mA} @ 100\text{Hz}$	Package	Radial, Can - Snap-In - 3 Lead
Tolerance $\pm 20\%$ Voltage - Rated $\pm 50\%$ ESR (Equivalent Series Resistance) ± 1.13 Ohm @ ± 100 Hz Lifetime @ Temp. ± 2000 Hrs @ $\pm 85\%$ C Operating Temperature ± 2000 Hrs @ $\pm 85\%$ C Polarization ± 2000 Polar Applications $\pm 20\%$ General Purpose Ripple Current - Low Frequency $\pm 20\%$	Series	B43305
Voltage - Rated 450V ESR (Equivalent Series Resistance) 1.13 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 970mA @ 100Hz	Capacitance	120μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 970mA @ 100Hz	Tolerance	±20%
Lifetime @ Temp. $2000 \text{Hrs} @ 85^{\circ} \text{C}$ Operating Temperature $-40^{\circ} \text{C} \sim 85^{\circ} \text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $970 \text{mA} @ 100 \text{Hz}$	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 970mA @ 100Hz	ESR (Equivalent Series Resistance)	1.13 Ohm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 970mA @ 100Hz	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 970mA @ 100Hz	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 970mA @ 100Hz	Polarization	Polar
11 7	Applications	General Purpose
	Ripple Current - Low Frequency	970mA @ 100Hz
Ripple Current - High Frequency -	Ripple Current - High Frequency	-
Impedance 1.59 Ohms	Impedance	1.59 Ohms
Lead Spacing 0.394" (10.00mm)	Lead Spacing	0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)	Size / Dimension	0.984" Dia (25.00mm)
Height - Seated (Max) 1.063" (27.00mm)	Height - Seated (Max)	1.063" (27.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

B43305B5127M82 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B5127M82 Payment Methods



















B43305B5127M82 Shipping Methods













If you have any question about B43305B5127M82, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com