

B43305C9477M80

lest a Quote

B43305C9477M80 Information

Heisener.com	Part Number	B43305C9477M80	
	Manufacturer	EPCOS (TDK)	l a se
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 470UF 20% 400V SNAP	<u>348</u>
	Package	Radial, Can - Snap-In	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305C9477M80 Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)200 Mrs @ 85°CDeprating Temperature2000 Hrs @ 85°CPolarizationGeneral PurposeRiple Current - High Frequency309 mOhmsRiple Current - High Frequency309 mOhmsLied Spacing309 mOhmsSiz / Dimension1.378° Dia (35.00mm)Size / Dimension1.378° Dia (35.00mm)Size / Dimension1.260° (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	_	
CapacitorsCapacitorsAckageRadial, Can - Snap-InPackageRadial, Can - Snap-InSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Size / Dimension1.378" Dia (35.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Manufacturer Part Number	B43305C9477M80
Aluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43305Capacitance470µFColerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzDiperating Temperature2000 Hrs @ 85°COperating Temperature640°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency2.05A @ 100HzRiple Current - High Frequency300 mOhmsLead Spacing309 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Package / CaseKadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance470µFColorance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency.05A @ 100HzRiple Current - High Frequency.05A @ 100HzSize / Dimension.390 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size.Package / CaseRadia, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzBipple Current - High Frequency-Size / Dimension1.378" Dia (35.00mm)Bisie / Dimension1.260" (32.00mm)Straface Mount Land Size-Potarge / CaseKalial, Can - Snap-In	Package	Radial, Can - Snap-In
Polerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarPolarizationsGeneral PurposeApplications2.05A @ 100HzRipple Current - Low Frequency2.05A @ 100HzImpedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Capacitance	470µF
ConstraintServerESR (Equivalent Series Resistance)290 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°CDerating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarPolarizationsGeneral PurposeApplications2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseReidi Acan - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	290 mOhm @ 100Hz
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.05A @ 100Hz
IOutputLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	390 mOhms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43305C9477M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305C9477M80 Payment Methods





If you have any question about B43305C9477M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com