

# B43504A2108M87

## B43504A2108M87 Information

Heisener (	Compare Number Manufacturer Category Description Package	B43504A2108M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference O	Dnly	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# B43504A2108M87 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Radial, Can - Snap-In   Package Radial, Can - Snap-In   Series B43504   Capacitance 1000µF   Tolerance ±20%   Voltage - Rated 250V   ESR (Equivalent Series Resistance) 130 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency -   Impedance -   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) 1.661" (42.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504A2108M87
Adminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance1000μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzLifed Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 1000µF   Tolerance ±20%   Voltage - Rated 250V   ESR (Equivalent Series Resistance) 130 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 2.8A @ 100Hz   Impedance -   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) -   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Pokage / CaseRatial, Can - Snap-In	Series	B43504
Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Capacitance	1000µF
ESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzBipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFunculationPackage / CaseRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 2.8A @ 100Hz   Ripple Current - High Frequency -   Impedance -   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) -   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	130 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.8A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency2.8A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.8A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.661" (42.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

### B43504A2108M87 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43504A2108M87 Payment Methods



If you have any question about B43504A2108M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com