

B43504B5277M002

B43504B5277M002 Information

	Manufact Category	Manufacturer Category Description	B43504B5277M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 450V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504B5277M002 Specifications

Manufacturer Part NumberB43504B5277M002ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43504Capacitance270µFTolerance±20%Voltage - Rated5000 mohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature440°C ~ 105°CPolariztionGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Size / Dimension1.378° Dia (35.00mm)Size / Dimension1.45°" (37.00mm)Gurface Mount Land Size-Mounting Type-Package / Case-Ripple Current - Low Frequency-Ripple Current - High Frequency-Size / Dimension1.378° Dia (35.00mm)Size / Dimension-Mounting Type-Package / Case-Ripple Current - Low Frequency-Size / Dimension1.45°" (37.00mm)Size / Dimension-Mounting Type-Size / Dimension-Mounting Type-Backage / Case-Mounting Type-Backage / Case-Mounting Type-Backage / Case-Backage / Case-Backage / Case-Backage / Case-Backage / Case-Backage / Case-	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-14A @ 100HzRipple Current - High Frequency-390 mOhmsLead Spacing3.378" Dia (35.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-40°C and Storem)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43504B5277M002
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzImpedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43504Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzInpedance590 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Mounting TypeThrough HolePoackage / CaseSatial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance270µFTolerance±20%Voltage - Rated450VBSR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzInpedance590 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.378° Dia (35.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Totance±0%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency590 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Series	B43504
Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzImpedance590 mOhmsIcad Spacing0.394" (10.00mn)Size / Dinension1.437" (37.00mn)Height - Seated (Max)1.457" (37.00mn)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	270µF
FSR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	500 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.4A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.4A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	590 mOhms
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report erro	Package / Case	Radial, Can - Snap-In - 3 Lead
Report end		Report errors?

B43504B5277M002 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504B5277M002 Payment Methods





If you have any question about B43504B5277M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com