



B43504D9227M82 Information

Heisener.com

Part Number B43504D9227M82
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 220UF 20% 400V SNAP

PackageRadial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43504D9227M82 Specifications

Manufacturer Part NumberB43504D9227M82ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzImpedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)	•	
Category Category Capacitors Aluminum Electrolytic Capacitors Radial, Can - Snap-In - 3 Lead Series Radial, Can - Snap-In - 3 Lead Series B43504 Capacitance 220µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 500 mOhms Lead Spacing Size / Dimension Height - Seated (Max) Capacitors Radial, Can - Snap-In - 3 Lead Sucal Su	Manufacturer Part Number	B43504D9227M82
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance220μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance220μFTolerance±20%Voltage - Rated400 VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)	Category	Capacitors
Series B43504 Capacitance 220μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.11A @ 100Hz Ripple Current - High Frequency - Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)		Aluminum Electrolytic Capacitors
Capacitance 220μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.11A @ 100Hz Ripple Current - High Frequency - Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.11A @ 100Hz Ripple Current - High Frequency - Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Series	B43504
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Inpedance Lead Spacing Output Size / Dimension Height - Seated (Max) A00V 400V 400 mOhm @ 100Hz -40°C ~ 105°C Operating Temperature -40°C ~ 105°C -40°C ~ 105°	Capacitance	220μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.11A @ 100Hz Ripple Current - High Frequency Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 1.071" (27.20mm)	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.11A @ 100Hz Ripple Current - High Frequency Impedance Lead Spacing 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 3000 Hrs @ 105°C -40°C ~ 105°C Foliations General Purpose 1.11A @ 100Hz	Voltage - Rated	400V
Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	ESR (Equivalent Series Resistance)	400 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.11A @ 100Hz Ripple Current - High Frequency - Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) General Purpose 1.11A @ 100Hz - 1.00Hz - 1.11A @ 100Hz - 1.11A @ 100Hz 1.11A @	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Applications	General Purpose
Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Ripple Current - Low Frequency	1.11A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.071" (27.20mm)	Impedance	500 mOhms
Height - Seated (Max) 1.071" (27.20mm)	Lead Spacing	0.394" (10.00mm)
	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	1.071" (27.20mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

B43504D9227M82 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504D9227M82 Payment Methods





















B43504D9227M82 Shipping Methods













If you have any question about B43504D9227M82, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com