



### **B43521A9108M000 Information**



For Reference Only

Part Number B43521A9108M000 Manufacturer EPCOS (TDK)

**Category** Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 1000UF 20% 400V RADIAL

Package Radial, Can - 5 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43521A9108M000 Specifications**

Manufacturer Part Number  Manufacturer  EPCOS (TDK)  Category  Capacitors  Aluminum Electrolytic Capacitors  Package  Radial, Can - 5 Lead  Series  B43521  Capacitance  1000µF  Tolerance  ±20%  Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  12000 Hrs @ 85°C  Operating Temperature  Polar  Applications  Rimple Current - Low Frequency  1200 Hrs @ 51A @ 100Hz	•	
Category  Capacitors  Aluminum Electrolytic Capacitors  Package  Radial, Can - 5 Lead  Series  B43521  Capacitance  1000µF  Tolerance  ±20%  Voltage - Rated  400V  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  12000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose	Manufacturer Part Number	B43521A9108M000
Aluminum Electrolytic CapacitorsPackageRadial, Can - 5 LeadSeriesB43521Capacitance $1000\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $90 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $12000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Manufacturer	EPCOS (TDK)
PackageRadial, Can - 5 LeadSeriesB43521Capacitance $1000μF$ Tolerance $±20%$ Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $90 mOhm @ 100Hz$ Lifetime @ Temp. $12000 Hrs @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral Purpose	Category	Capacitors
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		Aluminum Electrolytic Capacitors
Capacitance $1000 \mu F$ Tolerance $\pm 20\%$ Voltage - Rated $400 V$ ESR (Equivalent Series Resistance) $90 \text{ mOhm } @ 100 \text{Hz}$ Lifetime @ Temp. $12000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Package	Radial, Can - 5 Lead
Tolerance $\pm 20\%$ Voltage - Rated $400\text{V}$ ESR (Equivalent Series Resistance) $90 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $12000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Polarization Polar  Applications General Purpose	Series	B43521
Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $90 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $12000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Capacitance	1000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  12000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose	Tolerance	±20%
Lifetime @ Temp. $12000  \text{Hrs}  @  85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Voltage - Rated	400V
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	ESR (Equivalent Series Resistance)	90 mOhm @ 100Hz
Polarization Polar Applications General Purpose	Lifetime @ Temp.	12000 Hrs @ 85°C
Applications General Purpose	Operating Temperature	-40°C ~ 85°C
	Polarization	Polar
Ripple Current - Low Frequency 5.1A @ 100Hz	Applications	General Purpose
Rippie Current Low Frequency	Ripple Current - Low Frequency	5.1A @ 100Hz
Ripple Current - High Frequency -	Ripple Current - High Frequency	-
Impedance 110 mOhms	Impedance	110 mOhms
Lead Spacing -	Lead Spacing	-
Size / Dimension 1.575" Dia (40.00mm)	Size / Dimension	1.575" Dia (40.00mm)
Height - Seated (Max) 2.913" (74.00mm)	Height - Seated (Max)	2.913" (74.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - 5 Lead	Package / Case	Radial, Can - 5 Lead
Report errors?		Report errors?

#### **B43521A9108M000** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43521A9108M000 Payment Methods



















## B43521A9108M000 Shipping Methods













If you have any question about B43521A9108M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com