



B43584E2828M3 Information



For Reference Only

Part Number B43584E2828M3
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 8200UF 20% 200V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43584E2828M3 Specifications

Manufacturer Part Number B43584E2828M3 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance \$200µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance 8200µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43584E2828M3
Package Radial, Can - Screw Terminals Series B43584 Capacitance 8200μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package Radial, Can - Screw Terminals Series B43584 Capacitance \$200µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series B43584 Capacitance 8200µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 8200μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B43584
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Riow Home 17 mOhm @ 100Hz 15000 Hrs @ 85°C 6eneral Purpose 6eneral Purpose 15.2A @ 100Hz	Capacitance	8200μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 15000 Hrs @ 85°C -25°C ~ 85°C Polar -25°C ~ 85°C -25°C ~ 85°C -25°C ~ 85°C -20mOhms -24 (100Hz -24 (100Hz -24 (100Hz -24 (100Hz -25 (100Hz -25°C ~ 85°C -25°C ~ 85°C	Voltage - Rated	200V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	17 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 15.2A @ 100Hz Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance20 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	15.2A @ 100Hz
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	20 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.028" Dia (76.90mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.201" (106.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43584E2828M3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43584E2828M3 Payment Methods



















B43584E2828M3 Shipping Methods













If you have any question about B43584E2828M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com