

B43634B9337M000

B43634B9337M000 Information

| Contraction of the second seco | | B43634B9337M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact | |
|--|--------|--|-----------------|
| For Reference | e Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43634B9337M000 Specifications

| Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Radial, Can - Snap-In Package Radial, Can - Snap-In Series B43634 Capacitance 330µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 330 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 510 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.456" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can - Snap-In | | |
|---|------------------------------------|---|
| CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43634Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @100HzDoperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Manufacturer Part Number | B43634B9337M000 |
| Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43634Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency.195A @ 100HzRipple Current - High Frequency.100mm)Size / Dimension1.181° Dia (30.00mm)Size / Dimension1.456° (37.00mm)Height - Seated (Max).195m @ HoleSurface Mount Land Size-Package / CaseRadial, Can - Snap-In | Manufacturer | EPCOS (TDK) |
| PackageRadial, Can - Snap-InSeriesB43634Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-195A @ 100HzRiple Current - High Frequency510 mOhmsLad Spacing0.394" (10.00mm)Siz / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In | Category | Capacitors |
| SeriesB43634Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzLiad Spacing510 mOhnsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | | Aluminum Electrolytic Capacitors |
| Capacitance330µFColerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzImpedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Package | Radial, Can - Snap-In |
| Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In | Series | B43634 |
| Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzImpedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In | Capacitance | 330µF |
| ESR330 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In | Tolerance | $\pm 20\%$ |
| Lifetime @ Temp.8000 Hrs @ 85°CDoperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In | Voltage - Rated | 400V |
| Operating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | ESR (Equivalent Series Resistance) | 330 mOhm @ 100Hz |
| PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Lifetime @ Temp. | 8000 Hrs @ 85°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Operating Temperature | $-25^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$ |
| Ripple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Polarization | Polar |
| Ripple Current - High Frequency-Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Applications | General Purpose |
| Impedance510 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Ripple Current - Low Frequency | 1.95A @ 100Hz |
| IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Ripple Current - High Frequency | - |
| Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Impedance | 510 mOhms |
| Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Size / Dimension | 1.181" Dia (30.00mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Height - Seated (Max) | 1.456" (37.00mm) |
| Package / Case Radial, Can - Snap-In | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can - Snap-In |
| | | Report errors? |

B43634B9337M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43634B9337M000 Payment Methods



If you have any question about B43634B9337M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com