

B43644B5397M007

B43644B5397M007 Information

Heisener.com	 B43644B5397M007 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors ALUMINIUM ELECTROLYTIC SNAP-IN 4 Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43644B5397M007 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43644 Capacitance 390µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 1.8A @ 100Hz Ripple Current - High Frequency - Impedance 420 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.460" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	_	
CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43644Capacitance390µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzLifedine @ Jagating0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43644B5397M007
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43644Capacitance390µFTolerance±20%Voltage - Rated450 VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature44°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension1.460" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43644Capacitance390µFTolerance±20%Voltage - Rated450 VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension1.460" (37.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43644Capacitance390μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzLifedme @ Jamping0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance390µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)270 mOhm @ 100HzESR (Equivalent Series Resistance)5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Innedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzImpedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.460" (37.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43644
Voltage - Rated450VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzImpedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.460" (37.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Capacitance	390µF
EXR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzHinpedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.460" (37.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	270 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40° C ~ 105° C
Ripple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In Provide PropositionProvide Provide	Applications	General Purpose
Impedance420 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.8A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	420 mOhms
Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.460" (37.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43644B5397M007 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43644B5397M007 Payment Methods



If you have any question about B43644B5397M007, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com