

BFC238314514

Request a Quote

BFC238314514 Information

Heisener.com	Part Number	BFC238314514
	Manufacturer	Vishay BC Components
	Category	Capacitors Film Capacitors
	Description	CAP FILM 0.51UF 5% 400VDC RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC238314514 Specifications

Manufacturer Part NumberBFC238314514ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadialPackageMMKP383Capacitance051µFTolerance±5%Voltage Rating - AC00VVoltage Rating - DC400VDielectric Material>10ypoplene (PP), MetallizedOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.20° L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)IterminationPC InsApplications1.083" (27.50mm)Applications-Ap		
CategoryCapacitorsPackageRadialPackageRadialSeriesMMKP383Capacitance0.51µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropelne (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.220° L x 0.433° W (31.00mm x 11.00mm)Height - Seated (Max)0.827° (21.00mm)Lead Spacing1.083° (27.50mm)ApplicationsHigh Pulse, DV/DT	Manufacturer Part Number	BFC238314514
Filn CapacitorsPackageRadialSeriesMMKP383Capacitance0.51µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.220° L x 0.433° W (31.00mm x 11.00mm)Height - Seated (Max)0.827° (21.00mm)TerminationPC PinsLead Spacing1.083° (27.50mm)ApplicationsHigh Pulse, DV/DT	Manufacturer	Vishay BC Components
PackageRadialSeriesMMKP383Capacitance0.51µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material.Operating Temperature.55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max).0827" (21.00mm)Lead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Category	Capacitors
SeriesMMKP383Series0.51µFCapacitance0.51µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220° L x 0.433° W (31.00mm x 11.00mm)Height - Seated (Max)0.827° (21.00mm)Lead Spacing1.083° (27.50mm)ApplicationsHigh Pulse, DV/DT		Film Capacitors
Capacitance0.51µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyproylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220°L x 0.433°W (31.00mm x 11.00mm)Height - Seated (Max)0.827° (21.00mm)TerminationPC PinsLead Spacing1.083° (27.50mm)ApplicationsHigh Pulse, DV/DT	Package	Radial
Tolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Series	MMKP383
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Capacitance	0.51µF
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Voltage Rating - AC	200V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Voltage Rating - DC	400V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Operating Temperature	-55°C ~ 105°C
Size / Dimension1.220" L x 0.433" W (31.00mm x 11.00mm)Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Mounting Type	Through Hole
Height - Seated (Max)0.827" (21.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Package / Case	Radial
TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Size / Dimension	1.220" L x 0.433" W (31.00mm x 11.00mm)
Lead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DT	Height - Seated (Max)	0.827" (21.00mm)
Applications High Pulse, DV/DT	Termination	PC Pins
	Lead Spacing	1.083" (27.50mm)
Features -	Applications	High Pulse, DV/DT
	Features	-
Report errors		Report errors?

BFC238314514 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC238314514 Payment Methods



BFC238314514 Shipping Methods



If you have any question about BFC238314514, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com