

BFC246860183

BFC246860183 Information

Contraction and the second sec	BFC246860183 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.018UF RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC246860183 Specifications

Manufacturer Part Number BFC246860183 Manufacturer Vishay BC Components Category Capacitors Package Film Capacitors Package Radial Series MKT468 Capacitance 0.018µF Tolerance - Voltage Rating - AC - Voltage Rating - DC - Dielectric Material Polyester, Metallized SR (Equivalent Series Resistance) - Younging Type Stor 205°C 105°C Mounting Type Radial Size / Dimension - Size / Dimension 0.630° (16.00mm) Termination PC Pins Lead Spacing General Purpose Applications General Purpose	-	
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKT468Capacitance0.018µFTolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialSize / Dimension-Height - Seated (Max)0.630° (16.00mm)TerminationPC PinsLead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	BFC246860183
Film CapacitorsPackageRadialSeriesMKT468Capacitance0.018µFTolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.259" (7.50mm)ApplicationsGeneral PurposeFeatures-Features <t< td=""><td>Manufacturer</td><td>Vishay BC Components</td></t<>	Manufacturer	Vishay BC Components
PackageRadialSeriesMKT468Capacitance0.018µFTolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630° (16.00mm)Lead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-<	Category	Capacitors
SeriesMKT468Capacitance0.018µFTolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedDielectric Material-Ser (Equivalent Series Resistance)-Operating Temperature-Munting TypeRadialSize / Dimension-Height - Seated (Max)0.630° (16.00mm)IterninationDersingLead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-Start Seated Seated-Start Seated Seated Seated-Start Seated Seated Seated-Start Seated S		Film Capacitors
Capacitance0.018µFTolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedDielectric Material-SSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630° (16.00mm)TerminationPC PinsLead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-Fea	Package	Radial
Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeMailaPackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsApplications0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Series	MKT468
Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630° (16.00mm)Termination0.295° (7.50mm)Lead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.018µF
Voltage Rating - DC-Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Tolerance	-
Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	-
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C
Size / Dimension-Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	-
Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.630" (16.00mm)
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	General Purpose
Report errors	Features	-
		Report errors?

BFC246860183 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC246860183 Payment Methods



BFC246860183 Shipping Methods



If you have any question about BFC246860183, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com