

BKL6-S505-V-1-R

BKL6-S505-V-1-R Information

Heisener.com	Part Number Manufacturer Category Description Package	BKL6-S505-V-1-R Eaton Circuit Protection Fuses FUSE CERAMIC 1A 250V 5X20MM 5mm x 20mm (Axial) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BKL6-S505-V-1-R Specifications

ManufacturerEatonCategoryCircuit ProtectionFusesPackageSmm x 20mm (Axial)PackageS505Fuse TypeCartridge, CeramicCurrent RatingIAVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSmm x 20mm (Axial)Mounting TypeInrough HoleBreaking Capacity @ Rated Voltage1.5kAApprovalsBSI, CCC/QC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)		
CategoryCircuit ProtectionFusesPackage5mm x 20mm (Axial)SeriesS505Fuse TypeCartridge, CeramicCurrent Rating1AVoltage Rating - AC250VVoltage Rating - DC-Voltage Rating - DCSinm x 20mm (Axial)Package / CaseSinm x 20mm (Axial)Mounting TypeShowPackage / CaseSinm x 20mm (Axial)Mounting Type1.5kAApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Manufacturer Part Number	BKL6-S505-V-1-R
FusesPackage5mm x 20mm (Axial)SeriesS505Fuse TypeCartridge, CeramicCurrent Rating1AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting 12t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Manufacturer	Eaton
PackageSmm x 20mm (Axial)SeriesS505Fuse TypeCartridge, CeramicFuse TypeIACurrent RatingJS0VVoltage Rating - DC-Response TimeSlowPackage / CaseSimm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAApprovalsSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.18" Dia x 0.831" L (5.54mm x 21.10mm)	Category	Circuit Protection
SeriesS505Fuse TypeCartridge, CeramicCurrent RatingIAVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowMounting TypeSmm x 20mm (Axial)Mounting Type1.5kAMelting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)		Fuses
Fuse TypeCartridge, CeramicFuse Type1AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSim x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Package	5mm x 20mm (Axial)
Current RatingIAVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSmm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAAlting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Series	S505
Voltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC-Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Current Rating	1A
Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Voltage Rating - AC	250V
Package / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Voltage Rating - DC	-
Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Response Time	Slow
Breaking Capacity @ Rated Voltage1.5kAMelting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Package / Case	5mm x 20mm (Axial)
Melting I2t1.28ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Mounting Type	Through Hole
ApprovalsBSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Breaking Capacity @ Rated Voltage	1.5kA
Operating Temperature - Color - Size / Dimension 0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Melting I2t	1.28
Color - Size / Dimension 0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Approvals	BSI, CCC/CQC, CSA, cURus, IMQ, KC, PSE/JET, SEMKO, VDE
Size / Dimension 0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Operating Temperature	-
	Color	-
Report errors?	Size / Dimension	0.218" Dia x 0.831" L (5.54mm x 21.10mm)
		Report errors?

BKL6-S505-V-1-R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BKL6-S505-V-1-R Payment Methods



BKL6-S505-V-1-R Shipping Methods



If you have any question about BKL6-S505-V-1-R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com