



C146 11R024 601 8 Information



For Reference Only

Part Number C146 11R024 601 8

ManufacturerAmphenol Sine Systems CorpCategoryConnectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

Description CONN HOOD TOP ENTRY SZE24 M40

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C146 11R024 601 8 Specifications

| Manufacturer Part NumberC146 11R024 601 8ManufacturerAmphenol Sine Systems CorpCategoryConnectors, InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-Seriesheavy mate?, C146 MConnector TypeHoodStyleTop EntrySizeE24Lock LocationLocking Clip (2) on Base BottomThread SizeM40Size / Dimension4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm)Housing ColorGrayFeatures-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialAluminum, Die CastHousing FinishEMC CoatingOperating Temperature-40°C ~ 125°CReport errors? | | | |
|--|--------------------------|---|----------------|
| Category Connectors, Interconnects Heavy Duty Connectors - Housings, Hoods, Bases Package - Series heavy mate?, C146 M Connector Type Hood Style Top Entry Size E24 Lock Location Locking Clip (2) on Base Bottom Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Manufacturer Part Number | C146 11R024 601 8 | |
| Package - Series heavy mate?, C146 M Connector Type Hood Style Top Entry Size E24 Lock Location Locking Clip (2) on Base Bottom Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Manufacturer | Amphenol Sine Systems Corp | |
| Package - Series heavy mate?, C146 M Connector Type Hood Style Top Entry Size E24 Lock Location Locking Clip (2) on Base Bottom Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature | Category | Connectors, Interconnects | |
| Series heavy mate?, C146 M Connector Type Hood Style Top Entry Size E24 Lock Location Locking Clip (2) on Base Bottom Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | | Heavy Duty Connectors - Housings, Hoods, Bases | |
| Connector Type Hood Style Top Entry Size E24 Lock Location Locking Clip (2) on Base Bottom Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Package | - | |
| Style Top Entry Size E24 Lock Location Locking Clip (2) on Base Bottom Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Series | heavy mate?, C146 M | |
| Size E24 Lock Location Locking Clip (2) on Base Bottom Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Connector Type | Hood | |
| Lock LocationLocking Clip (2) on Base BottomThread SizeM40Size / Dimension4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm)Housing ColorGrayFeatures-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialAluminum, Die CastHousing FinishEMC CoatingOperating Temperature-40°C ~ 125°C | Style | Top Entry | |
| Thread Size M40 Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Size | E24 | |
| Size / Dimension 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) Housing Color Gray Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Lock Location | Locking Clip (2) on Base Bottom | |
| Housing Color Features Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Housing Finish EMC Coating Operating Temperature Gray -40°C ~ 125°C | Thread Size | M40 | |
| Features - Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Size / Dimension | 4.724" L x 1.693" W x 2.992" H (120.00mm x 43.00mm x 76.00mm) | |
| Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum, Die Cast Housing Finish EMC Coating Operating Temperature -40°C ~ 125°C | Housing Color | Gray | |
| Housing Material Housing Finish EMC Coating Operating Temperature Aluminum, Die Cast EMC Coating -40°C ~ 125°C | Features | - | |
| Housing Finish EMC Coating Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Ingress Protection | IP65 - Dust Tight, Water Resistant | |
| Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Housing Material | Aluminum, Die Cast | |
| | Housing Finish | EMC Coating | |
| Report errors? | Operating Temperature | -40°C ~ 125°C | |
| | | | Report errors? |

C146 11R024 601 8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C146 11R024 601 8 Payment Methods



















C146 11R024 601 8 Shipping Methods













If you have any question about C146 11R024 601 8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com