

C322C333K1R5CA

Request a Quote

C322C333K1R5CA Information

	Part Number	C322C333K1R5CA
www.heisener.com	Manufacturer	KEMET
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 0.033UF 100V X7R RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C322C333K1R5CA Specifications

Manufacturer Part Number C322C333K1R5CA Manufacturer KEMET Category Capacitors Ceramic Capacitors Ceramic Capacitors Package Radial Series Goldmax, 300 Capacitance 0.033µF Yoltage - Rated 0.003µF Operating Coefficient 410% Operating Temperature Coefficient X7R Operating Temperature - Applications General Purpose Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Spacing Formed Leads			
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance0.033µFTolerance±10%Voltage - Rated100VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-61erral PurposeApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / Case.20°U Lx 0.125°W (5.08mm x 3.18mm)Fielyt - Seated (Max).200°U Lx 0.125°W (5.08mm x 3.18mm)Height - Seated (Max).200°U Cs.08mm, 3.18mm)	Manufacturer Part Number	C322C333K1R5CA	
Ceramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance0.033µFTolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.0200° (5.08mm)Lead StyleFormed Leads	Manufacturer	KEMET	
PackageRadialSeriesGoldmax, 300Capacitance0.033µFTolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Size / Dimension0.200° (5.08mm)Height Seated (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads	Category	Capacitors	
Series Goldmax, 300 Capacitance 0.033µF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Noutring Type Through Hole Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200° (5.08mm) Lead Style Formed Leads		Ceramic Capacitors	
Capacitance0.033µFTolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Package	Radial	
Tolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeMindPackage / CaseRadialSize / Dimension0200° L x 0.125° W (5.08mm x 3.18mm)Hight - Seated (Max)-Hightension-High	Series	Goldmax, 300	
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeHolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing6.200" (5.08mm)Lead StyleFormed Leads	Capacitance	0.033μF	
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead SpacingFormed LeadsFormed Leads-	Tolerance	$\pm 10\%$	
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Head StyleFormed Leads	Voltage - Rated	100V	
Features.Ratings.ApplicationsGeneral PurposeFailure Rate.Mounting TypeThrough HolePackage / CaseRadiaSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max).Thickness (Max).Lead Spacing0.200" (5.08mm)Head Style.	Temperature Coefficient	X7R	
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Operating Temperature	-55°C ~ 125°C	
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Features	-	
Failure Rate-Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Ratings	-	
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Applications	General Purpose	
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Failure Rate	-	
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads	Mounting Type	Through Hole	
Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Package / Case	Radial	
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)	
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Height - Seated (Max)	0.260" (6.60mm)	
Lead Style Formed Leads	Thickness (Max)	-	
	Lead Spacing	0.200" (5.08mm)	
Report errors?	Lead Style	Formed Leads	
		Report errors?	

C322C333K1R5CA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C322C333K1R5CA Payment Methods



C322C333K1R5CA Shipping Methods



If you have any question about C322C333K1R5CA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com